## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: PHILIPS

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

## Model identifier: 8711500639561

## Type of light source:

| Lighting technology used:     | LFL_T5_HO | Non-directional or directional: | NDLS |  |  |
|-------------------------------|-----------|---------------------------------|------|--|--|
| Light source cap-type         | G5        |                                 |      |  |  |
| (or other electric interface) |           |                                 |      |  |  |
| Mains or non-mains:           | NMLS      | Connected light source (CLS):   | No   |  |  |
| Colour-tuneable light source: | No        | Envelope:                       | -    |  |  |
| High luminance light source:  | No        |                                 |      |  |  |
| Anti-glare shield:            | No        | Dimmable:                       | Yes  |  |  |
| Product parameters            |           |                                 |      |  |  |

|                                    |  | i iouuci para             | ineters   |              |  |  |
|------------------------------------|--|---------------------------|---|--------------|--|--|
| Parameter                          |  | Value                     | Parameter   | Value        |  |  |
| General product parameters:        |  |                           |   |              |  |  |
| • ·                                | mption in on-<br>000 h), rounded<br>est integer                                | 50                        | Energy efficiency<br>class  | G            |  |  |
| indicating if it<br>in a sphere (3 | bus flux (φuse),<br>refers to the flux<br>360º), in a wide<br>in a narrow cone | 4 375 in<br>Sphere (360°) | Correlated colour<br>temperature,<br>rounded to the<br>nearest 100 K,<br>or the range of<br>correlated colour<br>temperatures,<br>rounded to the<br>nearest 100 K, that<br>can be set | 4 000        |  |  |
| On-mode<br>expressed in W          | power (P <sub>on</sub> ),<br>/   | 49,3                      | Standby power (P <sub>sb</sub> ),<br>expressed in W<br>and rounded to the<br>second decimal   | 0,00         |  |  |
| for CLS, expre                     | ndby power (P <sub>net</sub> )<br>essed in W and<br>e second decimal           | -                         | Colour rendering<br>index, rounded to<br>the nearest integer,<br>or the range of CRI-<br>values that can be<br>set  | 80           |  |  |
| Outer                              | Height   | 1 463                     | Spectral power  | See image    |  |  |
| dimensions                         | Width  | 17                        | distribution in the   | in last page |  |  |
| without                            | Depth  | 17                        | =   |              |  |  |
|                                    | •  |                           |   | Dago 1 /     |  |  |

| separate<br>control gear,<br>lighting<br>control parts<br>and non-<br>lighting<br>control parts,<br>if any<br>(millimetre) |   | range 250 nm to 800<br>nm, at full-load |                |
|--|---|---|----------------|
| Claim of equivalent power <sup>(a)</sup>   | - | lf yes, equivalent power (W)            | -              |
|  |   | Chromaticity coordinates (x and y)      | 0,380<br>0,380 |

(a)<sub>'-'</sub> : not applicable;

(b)'-' : not applicable;

