

PRODUCT DATASHEET DALIECO LS/PD LI KIT

DALleco LS/PD LI | Sensors for light management systems



Areas of application

- Office luminaires
- Ceiling installation via LS/PD CI KIT possible

Product benefits

- VDE/VDE EMC certified system
- $V(\lambda)$ corrected light sensor element
- Individual activation/deactivation of light and presence sensor via remote control
- Presence detection angle adjustable between 40...90° via integrated shutters

Product features

- Light and presence sensor
- Presence detection via passive IR element
- Function indicator with two-color LED
- Integrated infrared remote control receiver
- Integrated pushbutton for automatic startup/deactivation of infrared receiver
- Halogen free polycarbonate plastic housing

TECHNICAL DATA

Electrical data

Mains frequency	0 Hz
-----------------	------

Dimensions & Weight

Length	48.00 mm
Width	15.00 mm
Height	17.00 mm
Product weight	33.00 g

Colors & materials

Temperatures & operating conditions

Capabilities

Dimmable	No
Dimming interface	DALI
Maximum installation height	5 m
Detection area	7 m ¹⁾
Detection angle	80 ° 2)
Type of installation	Ceiling integration/Luminaire integration
Operating range, light sensor	20800 tx ³⁾

¹⁾ Maximum diameter

Certificates & Standards

Approval marks – approval	CE
Protection class	II
Type of protection	IP20

DOWNLOAD DATA

	Documents and certificates
PDF	User instruction

²⁾ Approximately

³⁾ Approximately, measured at the sensor

Documents and certificates



Declarations Of Conformity CE

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321988652	Folding box 1	231 mm x 45 mm x 47 mm	69.00 g	0.49 dm ³
4008321789310	Shipping box 25	223 mm x 197 mm x 179 mm	1706.00 g	7.86 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.