

PRODUCT DATASHEET ST 171 SAFETY DEOS

Starters for single operation at 230 V AC (ST 111, ST 171, ST 173) | Starters for single operation at 230 V AC



Product features

- Temperature range for reliable cut-out: -20...+80 °C



TECHNICAL DATA

Electrical data

| | |
|-----------------|-------------|
| Nominal wattage | 65.00 W |
| Nominal voltage | 220...240 V |
| Mains frequency | 50/60 Hz |

Dimensions & Weight

| | |
|----------------|---------|
| Diameter | 21,5 mm |
| Product weight | 8.64 g |

Additional product data

| | |
|-----------------|---|
| Mercury content | 0.0 mg |
| Product remark | Temperature range for reliable switch-off: -20...+80 °C |

Capabilities

| | |
|----------|----|
| Dimmable | No |
|----------|----|

Country-specific categorizations

| | |
|-----------------|-----------------|
| Order reference | ST171SAFETY/220 |
|-----------------|-----------------|

Energy labelling regulation data acc EU 2019/2015

| | |
|--------|----------|
| Length | 40.30 mm |
| Height | 21,5 mm |
| Width | 21.50 mm |

DOWNLOAD DATA

Documents and certificates



Declarations Of Conformity CE

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4050300854106 | Unpacked 1 | 37 mm x 19 mm x 22 mm | 9.80 g | 0.02 dm ³ |
| 4050300797823 | Tray 25 | 111 mm x 43 mm x 113 mm | 232.80 g | 0.54 dm ³ |

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4050300797830 | Shipping box 200 | 227 mm x 98 mm x 227 mm | 2020.00 g | 5.05 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.