PHILIPS Lighting

MASTER TL5 High Output Xtra

MASTER TL5 HO Xtra 49W/840 SLV/20

This TL5 lamp (tube diameter 16 mm) combines the advantages of a TL5 High Output lamp (TL5 HO lamps are optimized for installations requiring high light output and offer excellent lumen maintenance and color rendering) with a long and reliable lifetime. This results in extra-low maintenance costs and saves on expensive spot replacement. Main applications are places where lamp replacement costs and/or costs of disruption are high.

Warnings and Safety

- Philips HF Xtreme gear ensures longest lifetime.
- To achieve lifetimes as published for 100% operation, dimming below 30% should not be applied.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data


General Information		Color rendering index (CRI)	80
Cap-Base	G5 [G5]		
Flux measurement reference	Sphere	Operating and Electrical	
		Power Consumption	50.0 W
Light Technical		Lamp Current (Nom)	0.255 A
Color Code	840 [CCT of 4000K]		
Luminous Flux	4,375 lumen	Controls and Dimming	
Color Designation	Cool White (CW)	Dimmable	Yes
Chromaticity Coordinate X (Nom)	0.38		
Chromaticity Coordinate Y (Nom)	0.38	Mechanical and Housing	
Correlated Color Temperature (Nom)	4000 K	Bulb Shape	T5 [16 mm (T5)]
Luminous Efficacy (rated) (Nom)	89 lm/W		

MASTER TL5 High Output Xtra

Approval and Application			
Mercury (Hg) Content (Max)	3 mg		
Mercury (Hg) Content (Nom)	3.0 mg		
Energy Consumption kWh/1000 h	50 kWh		
EPREL Registration Number	423,551		
Product Data			
Full product code	871150026253005		
Order product name	MASTER TL5 HO Xtra 49W/840 SLV/20		


Order code	927927784026		
Numerator - Quantity Per Pack	1		
Numerator - Packs per outer box	20		
Material number (12NC)	927927784026		
Full product name	MASTER TL5 HO Xtra 49W/840 SLV/20		
EAN/UPC - Case	8711500262608		

Dimensional drawing



Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL5 HO Xtra	17 mm	1,449.0 mm	1,456.1 mm	1,453.7 mm	1,463.2 mm
49W/840 SLV/20					


Photometric data



Spectral Power Distribution Colour - MASTER TL5 HO Xtra 49W/840 SLV/20

MASTER TL5 High Output Xtra

Lifetime



Life Expectancy Diagram - MASTER TL5 HO Xtra 49W/840 SLV/20

Lumen Maintenance Diagram - MASTER TL5 HO Xtra 49W/840 SLV/20



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, May 15 - data subject to change