## **Product Information Sheet**

dimensions

Width

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources	ELEGATED REGUL	-ATION (EU) 2019/20	ots with regard to energ	gy labelling of light			
Supplier's name or trade mark: PHILIPS							
Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL							
Model identifie	r: 9290024926						
Type of light so	urce:						
Lighting technology used:		LED	Non-directional or directional:	DLS			
Light source cap-type		GU5.3					
(or other electric interface)							
Mains or non-mains:		NMLS	Connected light source (CLS):	No			
Colour-tuneable light source:		No	Envelope:	-			
High luminance		No					
Anti-glare shield:		No	Dimmable:	Only with specific dimmers			
Product parameters							
Parameter		Value	Parameter	Value			
General product parameters:							
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		6	Energy efficiency class	F			
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		460 in Narrow cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000			
On-mode power (P <sub>on</sub> ), expressed in W		5,8	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00			
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal  Outer Height		<del>-</del> 46	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set  Spectral power	90 See image			
d:	. 1018110	70	dial dia dia dia dia	· i .			

51

distribution in the

in last page

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	51	range 250 nm to 800 nm, at full-load				
Claim of equivalent power <sup>(a)</sup>		Yes	If yes, equivalent power (W)	35			
			Chromaticity coordinates (x and y)	0,434 0,403			
Parameters for directional light sources:							
Peak luminous intensity (cd)		1 300	Beam angle in degrees, or the range of beam angles that can be set	36			
Parameters for LED and OLED light sources:							
R9 colour rendering index value		0	Survival factor	0,90			
the lumen maintenance factor		0,96					

(a)'-': not applicable;

(b)<sub>'-'</sub>: not applicable;

