

# LED T30

WOJ+14080

LED source LED T30 2 W with E-27 base and of an unusual shape. The unique design of the decorative MODERNSHINE series creates a warm atmospheric light effect, creating a pleasant atmosphere and mood lighting. It is characterised by a high light efficacy 120 lm/W. It is even more energy-efficient thanks to the use of durable COG filaments, which consume very little electricity. Wide beam angle 300° ensures even illumination of the room.



|                 |                      |                    |               |
|-----------------|----------------------|--------------------|---------------|
| Power           | <b>2 W</b>           | Voltage            | <b>230 V</b>  |
| Luminous flux** | <b>240 lm (360°)</b> | Colour temperature | <b>2400 K</b> |
| Colour of light | <b>WW</b>            | Beam angle         | <b>300 °</b>  |
| Socket          | <b>E27</b>           |                    |               |

## Technical data

---

|                              |               |
|------------------------------|---------------|
| Code                         | WOJ+14080     |
| Power                        | 2 W           |
| Nominal current              | 20 mA         |
| Voltage                      | 230 V         |
| Energy efficiency class      | E             |
| Energy consumption           | 2 kWh/1000h   |
| Frequency                    | 50HZ Hz       |
| Power factor                 | 0.4           |
| Useful luminous flux*        | 240 lm (360°) |
| Luminous flux**              | 240 lm (360°) |
| Lamp efficacy                | 120 lm/W      |
| Colour temperature           | 2400 K        |
| Colour of light              | WW            |
| Beam angle                   | 300 °         |
| RA                           | 80            |
| Uniformity of color SDCM max | 5             |
| Dimmable                     | No            |
| Working temperature range    | -20/+40 °     |
| Lifespan                     | 17000 h       |
| Socket                       | E27           |
| Dimension (AxBxC)            | 30x186 mm     |
| For use                      | Inside        |
| Application                  | INT           |
| Made in                      | PRC           |

## Related documents

---



 Declaration of Conformity

