



# CorePro GLASS LED candles and lusters

## CorePro LEDLusterND6.5-60W P45 E14840CLG

Featuring a classic heritage design, these filament LED candle combines the familiar shapes of classic incandescent bulbs with the benefits of long-lasting LED technology. The LED candle bulb, a very easy choice for people who are looking for a retrofit LED replacement, the LED candle provides 90% energy savings compared with conventional lamps. CorePro Glass LED bulbs provide excellent quality of light for stairway lighting. The LED candle bulb offers a lifetime of 15,000 hours to reduce maintenance costs.

### Product data

General Information		Operating and Electrical	
Cap-Base	E14	Line Frequency	50 to 60 Hz
Nominal lifetime	15,000 hour(s)	Input Frequency	50 to 60 Hz
Switching Cycle	20,000	Power Consumption	6.5 W
Lighting Technology	LED	Lamp Current (Nom)	50 mA
Flux measurement reference	Sphere	Wattage Equivalent	60 W
		Starting Time (Nom)	0.5 s
		Warm-up time to 60% light	0.5 s
		Power Factor (Fraction)	0.55
		Voltage (Nom)	220-240 V
Light Technical		Temperature	
Color Code	840 [CCT of 4000K]	T-Case Maximum (Nom)	55 °C
Luminous Flux	806 lm		
Color Designation	Cool White (CW)	Controls and Dimming	
Correlated Color Temperature (Nom)	4000 K	Dimmable	No
Luminous Efficacy (rated) (Nom)	124.00 lm/W		
Color Consistency	<6		
Color rendering index (CRI)	80		
LLMF At End Of Nominal Lifetime (Nom)	70 %		
Photobiological safety according to EN 62471	RG1		

# CorePro GLASS LED candles and lusters

## Mechanical and Housing

Bulb Finish	Clear
Bulb Shape	P45
Net Weight (Piece)	0.014 kg

## Approval and Application

Energy Efficiency Class	E
Energy Consumption kWh/1000 h	7 kWh
EPREL Registration Number	1825181
CE mark	Yes
EU RoHS compliant	Yes
Flickering value (PstLM) - Flickering value as per EN 61000-3-3	1
Stroboscopic effect visibility measure (SVM)	0.9


## Application Conditions

can it be used in closed luminaires	No
-------------------------------------	----

## Product Data



Order product name	CorePro LEDLusterND6.5-60W P45 E14840CLG
Full product name	CorePro LEDLusterND6.5-60W P45 E14840CLG
Full product code	871951434758800
Order code	929002028692
Material Nr. (12NC)	929002028692
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8719514347588
Numerator - Packs per outer box	10
EAN/UPC - Case	8719514347595

## Dimensional drawing



Product	D	C
CorePro LEDLusterND6.5-60W P45 E14840CLG	45 mm	80 mm

## Photometric data




Light Distribution Diagram - CorePro LEDLusterND6.5-60W P45 E14840CLG

General uniform lighting - CorePro LEDLusterND6.5-60W P45 E14840CLG


# CorePro GLASS LED candles and lusters

## Photometric data




Spectral Power Distribution Colour - CorePro LEDLusterND6.5-60W P45  
E14840CLG

## Lifetime



Lumen Maintenance Diagram - CorePro LEDLusterND6.5-60W P45  
E14840CLG



Life Expectancy Diagram

