

# LIMEA SLIM 2

SLI047006NW\_PW

See  
more

Hermetic luminaire LIMEA SLIM 2, with a power of 36 W, high light efficacy 175 lm/W. It is made of high-quality components, supported by a 5-year warranty. It has a very high degree of protection IP66, providing protection against the ingress of dust and water jets. IK08 class provides impact resistance. It shines with light of neutral - the most universal colour (4000K). Suitable for both surface and suspended mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.



Power	<b>36 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>6300 lm (360°)</b>	Colour temperature	<b>4000 K</b>
Colour of light	<b>Neutral white</b>	Beam angle	<b>120 °</b>
UGR	<b>22</b>	IK	<b>08</b>

## Technical data


---

Code	SLI047006NW_PW
Power	36 W
Nominal current	165 mA
Voltage	230 V
Energy consumption	36 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power factor	0.95
Useful luminous flux*	6300 lm (360°)
Luminous flux**	5200 lm (360°)
Lamp efficacy	175 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	120 °
UGR	22
RA	80
Light source included	+
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-30/+40 °
Lifespan	50000 h
Housing material	plastic
IK	08
Degree of protection (IP)	IP66
Colour	Gray/White
Dimension (AxBxC)	1700x65x67 mm
For use	Inside/Outside
Assembly method	On the ceiling, Suspended
Application	INT/EXT
Made in	PRC
Other	L80B10 50000h MTBF 80000h


## Related documents

---



 User manual



 Declaration of Conformity

