Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: PHILIPS

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

Model identifier: 9290024930

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type	GU5.3		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consum mode (kWh/100 up to the nearest	0 h), rounded	6	Energy efficiency class	F		
Useful luminous indicating if it ref in a sphere (360 cone (120º) or in (90º)	fers to the flux D ^o), in a wide	490 in Narrow cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000		
On-mode po expressed in W	ower (P _{on}),	5,8	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00		
Networked stand for CLS, express rounded to the se	sed in W and	_	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	90		
Outer	Height	46	Spectral power	See image		
dimensions	Width	51	distribution in the	in last page		

without D separate Control gear, lighting Control parts and non- lighting Control parts, if any (millimetre)	Depth	51	range 250 nm to 800 nm, at full-load	
Claim of equivalen	nt power ^(a)	Yes	lf yes, equivalent power (W)	35
			Chromaticity coordinates (x and y)	0,382 0,380
Parameters for dir	rectional light s	ources:		
Peak luminous inte	ensity (cd)	550	Beam angle in degrees, or the range of beam angles that can be set	60
Parameters for LE	D and OLED lig	ht sources:	1	
R9 colour renderin	ng index value	0	Survival factor	0,90
the lumen mainter	nance factor	0,96		
(a), , not applicable.			·	

(a)_{'-'} : not applicable;

(b)'-' : not applicable;

