


Tridon CCT



- IP66 rated die-cast aluminium wall light with opal polycarbonate diffuser suitable for commercial, hospitality and industrial applications
- Internal CCT selector switch allows the installer to choose the CCT between 3000K and 4000K at the point of installation
- Rear fixing points allowing the option for BESA box mounting
- Horizontal side pilot holes accepting 20mm surface conduit entries
- Tamper-proof stainless steel allen key screws
- Microwave sensor and Photocell options available
- Non-dimmable
- Powered by Tridonic



Black



Graphite

INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	SDCM	BEAM ANGLE	CLASS	IP	IK
220-240V	50/60Hz	-20°C to 25°C	L70 60,000	Ra 80	5	120°	1	IP66	IK09

CODE	DESCRIPTION	WATTAGE	CCT	LUMENS	LM/W	TRADE
ATRILED/B	CCT Selectable - Black	8W	3000/4000K	701lm(4000K)	88lm(4000K)	£102.00
ATRILED/G	CCT Selectable - Graphite					£102.00

CODE (OPTIONS)	DESCRIPTION	TRADE	CODE (OPTIONS)	DESCRIPTION	TRADE
/PC	Electronic Photocell	+ £36.00	/MWS	Integral Microwave Sensor	+ £48.00