PHILIPS Lighting



CorePro Plastic LEDcandles & lusters

CorePro candle ND 5-40W E14 865 B35 FR

The CorePro LEDcandles and lusters are designed for retrofit replacement of incandescent lamps and are particularly attractive for chandeliers. They are compatible with fixtures with an E14 holder for candles and E14 or E27 holders for lusters and are available in multiple color temperatures. LED lamps deliver huge energy savings of up to 80% energy-saving compared with halogen lamps and provide excellent quality of light. By offering a lifetime of 15,000 hours it lowers maintenance costs. The CorePro LED candles and lusters are perfect for your basic lighting needs.

Product data

General Information	
Cap-Base	E14 [E14]
Nominal lifetime	15,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
Light Technical	
Color Code	865 [CCT of 6500K]
Luminous Flux	470 lumen
Color Designation	Cool Daylight
Correlated Color Temperature (Nom)	6500 K
Luminous Efficacy (rated) (Nom)	94.00 lm/W
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %


Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	5 W
Lamp Current (Nom)	44 mA
Wattage Equivalent	40 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.51
Voltage (Nom)	220-240 V
Temperature	
T-Case Maximum (Nom)	81 °C
Controls and Dimming	
Dimmable	No

CorePro Plastic LEDcandles & lusters

Mechanical and Housing	
Bulb Finish	Frosted
Bulb Shape	B35 [B 35mm]
Approval and Application	
Energy Consumption kWh/1000 h	5 kWh
EPREL Registration Number	453,201
CE mark	Yes
EU RoHS compliant	Yes
Product Data	
Full product code	871951431258600


Order product name	CorePro candle ND 5-40W E14 865 B35 FR
Order code	929002969202
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material number (12NC)	929002969202
Full product name	CorePro candle ND 5-40W E14 865 B35 FR
EAN/UPC - Case	8719514312593

Dimensional drawing



ProductDCCorePro candle ND 5-40W E14 865 B35 FR35 mm106 mm


Photometric data



Spectral Power Distribution Colour - CorePro candle ND 5-40W E14 865 B35 FR


CorePro Plastic LEDcandles & lusters

Photometric data



Light Distribution Diagram - CorePro candle ND 5-40W E14 865 B35 FR

Lifetime



Life Expectancy Diagram - CorePro candle ND 5-40W E14 865 B35 FR

Lumen Maintenance Diagram - CorePro candle ND 5-40W E14 865 B35 FR



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, May 22 - data subject to change