

PRODUCT-DETAILS

U61

U61 U Compact distribution board, Flush-mounted, 72 SU, Geïsoleerd, IP31, Field Width: 1, Rows: 6, 984 mm x 310 mm x 120 mm



Algemene informatie

Type	U61
Artikelnummer	2CPX030110R9999
EAN	4011617301103

Omschrijving U61 U Compact distribution board, Flush-mounted, 72 SU, Geïsoleerd, IP31, Field Width: 1, Rows: 6, 984 mm x 310 mm x 120 mm

Omschrijving Compact distribution board, series U, partly assembled cabinet, for the internal use, with closed doorframe and door, class of protection II (double insulated), in combination with earthing set (accessory) we can achieve protection class 1, degree of protection IP31, applicable standards: EN 61439-1, EN 61439-3, Rated operational voltage 400V AC 50/60 Hz, rated current 125 A, Powder-coated, in RAL 9016, enclosure out of sheet steel, metal door, door out of sheet steel, in RAL 9016, with Standard closure, door opening angle 120 degree, door hinge right or left, cable entry on top via nippel flange included, on bottom via flange opening pre-punched, dimensions in mm (H x W x D): 984 x 310 x 120, Shutter frame dimensions in mm (H x W x D): 994 x 354 x 27, Grid unit 6 GU, panel width 1, 6-rows, Space units 72, Row distance in mm: 125, covers out of Plastic, 90 degree press and turn closure, RAL 7035, with N/PE Quick-terminal, cable fastening rail integrated, expanded with distributor fields, device support removable

Technical

Normen	DIN EN 61439-3
Nominaal bedrijfsvoltage	Maximum 400 V
Operationeel voltage	400 V

Toegekende stroom (I_n)	125 A
Vermogensverlies	$\Delta t = 20K$ 32.9 W $\Delta t = 25K$ 43.4 W $\Delta t = 30K$ 54.4 W
Aantal rijen	6
Design	Wall cabinet flush-mount
Type sluiting	Turn Handle
Configuratietype	expanded with distributor fields
Afdekplaattype	Door
Behuizingstype	compact distribution boards
Montagetype	Flush-mounted
Deurtype	Enkele deur
Uitvoering oppervlakte	Powder-coated
Materiaal behuizing	Steel
Plaats van inbouw	Wall cabinet flush-mount
Afdekestijl	Closed
DIN-plaatseenheden	72
Meterborden	0
RAL-nummer	RAL 9016 - Verkeerswit
Kleur	Traffic white
Terminaltype	Quick-Terminal

Environmental

Beschermingsgraad	IP31
Beschermingsklasse	Geïsoleerd
RoHS-status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS-informatie	9AKK107992A8144
REACH-verklaring	2CPC100005X0201
SCIP	d7943dab-b777-483d-8993-cc363505075c Germany (DE)
Rapport over conflictmineralen (CMRT)	9AKK108468A3363

Dimensions

Breedte in module-eenheden	12
Product netto breedte	310 mm
Product netto hoogte	984 mm
Product netto diepte	120 mm
Product netto gewicht	14.347 kg
Inbouwdiepte (t_2)	120 mm

Ordering

Minimale bestelhoeveelheid	1 stuk
----------------------------	--------

Pakketniveau 1 Units	pack 1 stuk
Pakketniveau 1 Brutogewicht	14.976 kg
Vervangen product-ID (NIEUW)	2CPX052609R9999

Certificates and Declarations

Conformiteitsverklaring - CE	9AKK107992A8144
---------------------------------	-----------------

Installation

Instructies en handleidingen	2CPC100502M5601 2CPC130114M5601
---------------------------------	------------------------------------

Popular Downloads

Gegevensblad, technische informatie	2CPC000001C0101 2CPC000002C0101 2CPC000377C0101
Building Information Modeling – BIM	9AKK107680A4551

Classifications

ETIM 8	EC000214 - Installatiekast met DIN-rail leeg
ETIM 9	EC000214 - Installatiekast met DIN-rail leeg
WEEE-categorie	4. Large Equipment (Any External Dimension More Than 50 cm)
AEEA B2C / B2B	Business To Consumer
CN8	85381000
eClass	V11.0 : 27142409
Object classificatiecode	U

Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
2CPX052497R9999	CZL62 U Earthing set, 15 mm x 125 mm x 280 mm	CZL62	1	piece
2CPX052412R9999	CZT2 ComfortLine Accessory door, 165 mm x 62 mm x 32 mm	CZT2	1	piece
2CPX052488R9999	CZT5 ComfortLine Accessory door, 164 mm x 62 mm x 47 mm	CZT5	1	piece
2CPX038228R9999	ZA5 Enclosure accessories, 210 mm x 200 mm x 3 mm	ZA5	1	piece
2CPX063132R9999	ZK220 ZK Terminals, 71 mm x 213 mm x 52 mm	ZK220	1	piece
2CPX062745R9999	ZK50BT Terminals	ZK50BT	1	piece
2CPX062446R9999	ZKV200P4 ZKV Enclosure accessories, 30 mm x 75 mm x 100 mm	ZKV200P4	1	piece
2CPX038148R9999	ZKV201 Interior fitting system	ZKV201	1	piece
2CPX052419R9999	CZT26H ComfortLine Enclosure accessories, 500.5 mm x 29.5 mm x 5 mm	CZT26H	1	piece
2CPX010487R9999	TZ503 Enclosure accessories, 70 mm x 100 mm x 180 mm	TZ503	1	piece
2CPX010488R9999	TZ504 Enclosure accessories, 70 mm x 100 mm x 180 mm	TZ504	1	piece
2CPX010489R9999	TZ505 Enclosure accessories, 70 mm x 100 mm x 180 mm	TZ505	1	piece
2CPX010490R9999	TZ506 Enclosure accessories, 70 mm x 100 mm x 180 mm	TZ506	1	piece
2CPX010491R9999	TZ507 Enclosure accessories, 25 mm x 100 mm x 170 mm	TZ507	1	piece
2CPX010492R9999	TZ508 Enclosure accessories, 25 mm x 100 mm x 170 mm	TZ508	1	piece

Categorieën

Laagspanningsproducten en -systemen → Verdelers → Onderverdeeldborden (System pro E energy) → Compacte verdeeldborden - samengestelde modules → U

