

---

PRODUCT-DETAILS

# HSB375

## SHRINK KON BOX - 6,5M BLACK



---

### General Information

|                       |  |
|-----------------------|--|
| Extended Product Type | HSB375   |
| Product ID            | 7TCA017300R0343  |
| EAN                   | 5414363104278  |
| Catalog Description   | SHRINK KON BOX - 6,5M BLACK  |
| Long Description      | Thin Wall Heat Shrink Tubing in Dispenser Box - 3/8 Inch Expanded Inside Diameter - 6.5 Meters, Black, Shrink Ratio 2:1, CrossLinked Polyolefin, Item is Silicone, Cadmium and Lead Free |

---

### Ordering

|                         |               |
|-------------------------|---------------|
| EAN                     | 5414363104278 |
| UPC                     | 786210634265  |
| Country of Origin       | Germany (DE)  |
| Selling Unit of Measure | each          |

---

### Dimensions

|                            |                   |
|----------------------------|-------------------|
| Product Net Depth / Length | 21.32 in<br>6.5 m |
|----------------------------|-------------------|

---

### Container Information

|                                |                   |
|--------------------------------|-------------------|
| Package Level 1 Units          | 1 piece           |
| Package Level 1 Width          | 2.4 in<br>61 mm   |
| Package Level 1 Height         | 6.7 in<br>170 mm  |
| Package Level 1 Depth / Length | 6.7 in<br>170 mm  |
| Package Level 2 Units          | 60 piece          |
| Package Level 2 Width          | 15.8 in<br>401 mm |
| Package Level 2 Height         | 22.5 in<br>572 mm |
| Package Level 2 Depth / Length | 20.9 in<br>531 mm |

### Additional Information

|                            |                                  |
|----------------------------|----------------------------------|
| Brand / Label              | Shrink-Kon                       |
| Color                      | Black                            |
| Dielectric Test Voltage    | 280/Mil (11kV/mm) V              |
| Effective Date             | 19980621                         |
| Flammability Hazard Rating | Self Extinguishing               |
| Process Temperature Rating | -67 to +212 °F<br>-55 to +100 °C |
| Product Name               | PLASTIC CONDUIT                  |
| Product Type               | Thin-Wall Heat Shrinkable Tubing |
| RoHS Date                  | 9AKK107992A8965                  |
| Shrink Ratio               | 2:1                              |
| Shrink Temperature         | 230 °F<br>110 °C                 |
| Thickness                  | Thin                             |
| Water Absorption           | 0.03%                            |

### Certificates and Declarations

|                                   |        |
|-----------------------------------|--------|
| Data Sheet, Technical Information | HSB375 |
|-----------------------------------|--------|

### Classifications

|                                    |                              |
|------------------------------------|------------------------------|
| ETIM 6                             | EC000217 - Shrink tubing     |
| ETIM 7                             | EC000217 - Shrink tubing     |
| ETIM 8                             | EC000217 - Shrink tubing     |
| UNSPSC                             | 39121723                     |
| WEEE Category                      | Product Not in WEEE Scope    |
| IDEA Granular Category Code (IGCC) | 5073 >> Heat shrinkable tube |

### Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Identification & Heat Shrink

