

# SYSTEM SHIFT - GRID M

WLD+40041

See  
more

On track luminaire SYSTEM SHIFT - GRID M, with a power of 17 W, high light efficacy 100 lm/W. It is made of high-quality components, supported by a 5-year warranty. It also stands out for its very high colour rendering index RA>90. It shines with a warm light (3000K), which promotes relaxation and rest, making the illuminated room cosier. Narrow beam angle 35° gives directional light so that selected objects or surfaces can be better exposed. Designed to be mounted on a track.



|                           |               |                 |               |
|---------------------------|---------------|-----------------|---------------|
| Power                     | <b>17 W</b>   | Voltage         | <b>48 V</b>   |
| Colour temperature        | <b>3000 K</b> | Colour of light | <b>WW</b>     |
| Beam angle                | <b>35 °</b>   | UGR             | <b>&lt;19</b> |
| Degree of protection (IP) | <b>IP20</b>   |                 |               |

## Technical data


---

|                              |                |
|------------------------------|----------------|
| Code                         | WLD+40041      |
| Power                        | 17 W           |
| Nominal current              | 350 mA         |
| Voltage                      | 48 V           |
| Energy consumption           | 17 kWh/1000h   |
| Frequency                    | DC Hz          |
| Protection class             | III            |
| Power factor                 | 1              |
| Useful luminous flux*        | 1700 lm (360°) |
| Luminous flux**              | 1000 lm (360°) |
| Lamp efficacy                | 100 lm/W       |
| Luminous intensity           | 3100 cd        |
| Colour temperature           | 3000 K         |
| Colour of light              | WW             |
| Beam angle                   | 35 °           |
| UGR                          | <19            |
| RA                           | >90            |
| Light source included        | Yes            |
| Producer of LED diodes       | osram          |
| Uniformity of color SDCM max | 5              |
| Dimmable                     | No             |
| Working temperature range    | -20 to +40 °   |
| Lifespan                     | 50000 h        |
| Housing material             | AL+PC          |
| Degree of protection (IP)    | IP20           |
| Colour                       | White          |
| Dimension (AxBxC)            | 303x23x42 mm   |
| For use                      | Inside         |
| Assembly method              | NA SZYŃĘ       |
| Application                  | Inside         |
| Made in                      | PRC            |

## Related documents

---



 User manual





 Declaration of Conformity




 Photometric file





 3D model

48V 



Die Montage erfolgt über ein einfaches Klick-System  
zusätzlich lässt sich die Leuchte je nach Bedarf verschieben

48V 



Die Montage erfolgt über ein einfaches Klick-System  
zusätzlich lässt sich die Leuchte je nach Bedarf verschieben

