

PRODUCT-DETAILS

CB1-621B

CB1-621B Buzzer



General Information

| | |
|-----------------------|--|
| Extended Product Type | CB1-621B |
| Product ID | 1SFA619600R6216 |
| EAN | 7320500556894 |
| Catalog Description | CB1-621B Buzzer |
| Long Description | <p>The CB1-621B Buzzer is: Compact - Buzzer - Continuous sound without light - Black - Non-illuminated - 110 ... 130 V</p> <p>This Buzzer is part of ABB's compact range, the most efficient all-in-one solution available, reducing installation time and cost.</p> <p>The compact range has a high level of dust and water resistance.</p> |

Ordering

| | |
|------------------------|----------|
| Minimum Order Quantity | 10 piece |
| Customs Tariff Number | 85369001 |

Popular Downloads

| | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SFC151007C02__ |
| Instructions and Manuals | 1SFC151011M0201 |

Dimensions

| | |
|----------------------------|----------|
| Product Net Width | 0.03 m |
| Product Net Height | 0.03 m |
| Product Net Depth / Length | 0.055 m |
| Product Net Weight | 0.021 kg |

Technical

| | |
|---------------------------|--|
| Ambient Air Temperature | Operation -25 ... +70 °C Storage -40 ... +85 °C |
| Color | Black |
| Illumination | Non-illuminated |
| Function | Continuous sound without light |
| Degree of Protection | Front IP66 Front IP67 Front IP69K Terminals IP20 |
| Enclosure Type NEMA | Type1 Type12 Type13 Type3R Type4 Type4X |
| Pollution Degree | 3 |
| Rated Frequency (f) | 50 / 60 Hz |
| Rated Operational Voltage | Supply Circuit 110 ... 130 V AC |
| Sound dB (A) | 80 dB |
| Connecting Capacity | Flexible with Ferrule 1 x 0.75...2.5 mm ² Flexible with Ferrule 2 x 0.75...2.5 mm ² Flexible with Insulated Ferrule 1 x 0.75...2.5 mm ² Flexible with Insulated Ferrule 2 x 0.75...2.5 mm ² Flexible 1 x 0.75 ... 2.5 mm ² Flexible 2 x 0.75 ... 2.5 mm ² Solid 1 x 0.75...2.5 mm ² Solid 2 x 0.75...2.5 mm ² |
| Connection Type | Screw Clamp |
| Terminal Type | Screw Terminals |
| Tightening Torque | 0.9 N·m |
| Wire Stripping Length | 8 mm |

Technical UL/CSA

| | |
|---------------------|----------------|
| Connecting Capacity | 1x 18...14 AWG |
| UL/CSA | 2x 18...14 AWG |

Environmental

| | |
|------------------|--|
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| RoHS Date | 635 4 |
| RoHS Information | 2CMT2015-005451 |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B | Business To Business |

Certificates and Declarations

| | |
|----------------------------------|---------------------|
| CB Certificate | CQC_CN_CN50749 |
| CQC Certificate | CQC2003010305054693 |
| cURus Certificate | UL_E496500-20171020 |
| Declaration of Conformity - CCC | 2020980305001187 |
| Declaration of Conformity - CE | 2CMT2015-005451 |
| Declaration of Conformity - UKCA | 2CMT2020-006121 |
| DNV GL Certificate | 9AKK107046A3749 |

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Units | bag 10 piece |
| Package Level 1 Width | 0.05 m |
| Package Level 1 Depth / Length | 0.235 m |
| Package Level 1 Height | 0.125 m |
| Package Level 1 Gross Weight | 0.214 kg |
| Package Level 1 EAN | 7320500401750 |

Classifications

| | |
|------------------------------------|-------------------------------|
| Object Classification Code | P |
| ETIM 6 | EC001026 - Acoustic indicator |
| ETIM 7 | EC001026 - Acoustic indicator |
| ETIM 8 | EC001026 - Acoustic indicator |
| eClass | V11.0 : 27371214 |
| UNSPSC | 46171607 |
| IDEA Granular Category Code (IGCC) | 7389 >> Buzzers |
| E-Number (Finland) | 2313713 |
| E-Number (Sweden) | 3705816 |

Categories

Low Voltage Products and Systems → Control Products → Pilot Devices → Compact Range

