

# PRODUCT DATASHEET ENDURA Style Crystal 80cm Post 4.5W

ENDURA STYLE CRYSTAL | Stainless steel wall luminaires and bollards with indirect illumination



#### Areas of application

- Building facades
- Entrance lighting
- Patios, balconies

#### **Product benefits**

- Easy and quick installation
- Energy-efficient thanks to LED technology

#### **Product features**

- Bright and functional outdoor LED luminaires
- Available with and without motion sensor
- Stainless steel housing
- Type of protection: IP44



## **TECHNICAL DATA**

## Electrical data


| Nominal wattage        | 4.50 W        |
|------------------------|---------------|
| Nominal voltage        | 220240 V      |
| Mains frequency        | 5060 Hz       |
| Power factor $\lambda$ | > 0.5         |
| Protection class       | 1             |
| Operating mode         | Mains voltage |

## Photometrical data

| Luminous flux                                  | 400 lm     |  |
|------------------------------------------------|------------|--|
| Total luminous flux of contained light sources | 500 lm     |  |
| Luminous efficacy                              | 89 lm/W    |  |
| Color temperature                              | 3000 K     |  |
| Light color (designation)                      | Warm White |  |
| Color rendering index Ra                       | ≥80        |  |
| Standard deviation of color matching           | < 6 sdcm   |  |

# **Dimensions & Weight**

| Length         | 80.00 mm  |
|----------------|-----------|
| Width          | 80.00 mm  |
| Height         | 800.00 mm |
| Product weight | 1930.00 g |



## Materials & Colors

| Product color   | Steel                         |
|-----------------|-------------------------------|
| Housing color   | Steel                         |
| Body material   | Steel                         |
| Cover material  | Polymethylmethacrylate (PMMA) |
| Mercury content | 0.0 mg                        |

## **Application & Mounting**

| Ambient temperature range | -20+40 °C                   |
|---------------------------|-----------------------------|
| Type of connection        | Terminal, 3-Pole (L, N, PE) |
| Type of protection        | IP44                        |
| Dimmable                  | No                          |
| Mounting type             | Surface                     |
| Mounting location         | Ground                      |
| Application environment   | Outdoor                     |
| LED module replaceable    | Not replaceable             |
| With light source         | Yes                         |

## Lifespan

| Lifespan L70/B50 at 25 °C  | 25000 h <sup>1)</sup> |  |
|----------------------------|-----------------------|--|
| Number of switching cycles | 12500                 |  |

<sup>1)</sup> \_t[h]: L70 / B50 @ 25 °C (Ta), \_t[h]: L80 / B10 @ 25 °C (Ta), \_t[h]: L90 / B10 @ 25 °C (Ta)

## **Certificates & Standards**

| Standards                                            | CE / EAC / UKCA |
|------------------------------------------------------|-----------------|
| Luminaire with limited surface temperature, "D sign" | No              |

# **EQUIPMENT / ACCESSORIES**

- Complete mounting and connecting accessories included

## **DOWNLOAD DATA**

|     | Documents and certificates |
|-----|----------------------------|
| PDF | User instruction           |
| PDF | Packaging insert           |

|     | Documents and certificates      |
|-----|---------------------------------|
| PDF | Declarations Of Conformity CE   |
| PDF | Declarations Of Conformity UKCA |

## **LOGISTICAL DATA**

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075474239 | Folding box<br>1             | 107 mm x 107 mm x 824 mm             | 2109.00 g    | 9.43 dm <sup>3</sup>  |
| 4058075474246 | Shipping box<br>6            | 335 mm x 230 mm x 840 mm             | 18468.00 g   | 64.72 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.