PRODUCT DATASHEET
L 30W 840

LUMILUX® T8 | Tubular fluorescent lamps 26 mm, with G13 bases

Areas of application

– Public buildings
– Office lighting
– Industry
– Shops
– Supermarkets and department stores
– Street lighting
– Outdoor applications only in suitable luminaires

Product benefits

– Proven lamp technology

Product features

– Very good lumen maintenance: 90 % throughout the service lifetime of the lamp
– Good color rendering index
– Dimmable

TECHNICAL DATA

Electrical data

Nominal wattage	30 W
Construction wattage	30.00 W
Nominal voltage	220 V
Nominal current	365 mA

Photometrical data

Luminous flux	2400 lm
Luminous efficacy	80 lm/W
Light color (designation)	Neutral White
Color temperature	4000 K
Color rendering index Ra	≥80
Light color	840

Dimensions & Weight

Overall length	895.00 mm
Diameter	26.00 mm
Product weight	124.00 g

Additional product data

Base (standard designation)	G13
Mercury content	3.0 mg
Design / version	Frosted

Capabilities

Dimmable	No

Certificates & Standards

Energy efficiency class	A
Energy consumption	36.00 kWh/1000h

Country-specific categorizations

Order reference	L 30W/840

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G13

Length	895.00 mm
Height	26.00 mm
Width	26.00 mm

Safety advice

– In case of lamp breakage: www.ledvance.com/brokenlamp

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075693173	Sleeve 1	905 mm x 28 mm x 27 mm	140.00 g	0.68 dm³
4058075693180	Shipping box 25	929 mm x 150 mm x 155 mm	3826.00 g	21.60 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.