

# LED MR11 GU10

WOJ+14106

LED source LED MR11 GU10 4 W with the popular GU10 mount. It shines with a warm light (3000K), which promotes relaxation and rest, making the illuminated room cosier. Narrow beam angle 45° gives directional light so that selected objects or surfaces can be better exposed.



Power	<b>4 W</b>	Voltage	<b>230 V</b>
Luminous flux**	<b>320 lm (360°)</b>	Colour temperature	<b>3000 K</b>
Colour of light	<b>WW</b>	Beam angle	<b>45 °</b>
Socket	<b>GU10</b>		

## Technical data


---

Code	W0J+14106
Power	4 W
Nominal current	30 mA
Voltage	230 V
Energy efficiency class	G
Energy consumption	4 kWh/1000h
Frequency	50HZ Hz
Power factor	0,5
Useful luminous flux*	260 lm (90°)
Luminous flux**	320 lm (360°)
Lamp efficacy	80 lm/W
Luminous intensity	330 cd
Colour temperature	3000 K
Colour of light	WW
Beam angle	45 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Socket	GU10
Dimension (AxBxC)	35x48 mm
For use	Inside
Application	INT
Made in	PRC


## Related documents

---



 Declaration of Conformity



 Photometric file