



Ledinaire SlimDownlight

DN065C G4 LED12/830 12W 220-240V 6-D175

The LEDINAIRE range contains a selection of popular off-the-shelf LED luminaires that come with the high Philips quality levels at a competitive price. Reliable, energy-efficient and affordable – just what you need

Product data

General Information	
Light source color	830 warm white
Light source replaceable	No
Driver included	Yes
Luminaire light beam spread	110°
Connection	Screw connection block 2-pole
Protection class IEC	Safety class II
Flammability mark	For mounting on normally flammable
	surfaces
CE mark	CE mark
Warranty period	3 years
Constant light output	No
Number of products on MCB of 16 A type B	74
EU RoHS compliant	Yes
Light source engine type	LED
Unified glare rating CEN	28
Lighting Technology	LED
Brand	Philips
Light Technical	
Luminous Flux	1,200 lumen

Luminous Efficacy (rated) (Nom)	100 lm/W
Color rendering index (CRI)	80
Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 or 60 Hz
Input Frequency	50 or 60 Hz
Power Consumption	12 W
Inrush current	3.85 A
Power Factor (Fraction)	0.9
Temperature	
Ambient temperature range	-20 to +40 °C
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Housing Material	Metal-Plastic
Reflector material	-
Housing Color	White

Ledinaire SlimDownlight


Overall length	175 mm	
Overall width	175 mm	
Overall height	27 mm	
Overall diameter	175 mm	
Dimensions (Height x Width x Depth)	NaN x NaN x NaN mm	
Approval and Application		
Ingress protection code	IP20/40 [Finger-protected, Emitting	
	surface]	
Mech. impact protection code	IK03 [0.3 J]	
Initial Performance (IEC Compliant)		
Luminous flux tolerance	+/-10%	
Init. Corr. Color Temperature	3000 K	
Power consumption tolerance	+/-10%	
Over Time Performance (IEC Compliant)		
Lumen maintenance at median useful life*	L65	

Product Data	
Full product code	871951446447600
Order product name	DN065C G4 LED12/830 12W 220-240V 6-
	D175
Order code	929003251532
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material number (12NC)	929003251532
Net weight	0.380 kg
Full product name	DN065C G4 LED12/830 12W 220-240V 6-
	D175
EAN/UPC - Case	8719514464483




50000 h


Dimensional drawing



Photometric data



Philips Lighting B.V.



Light Distribution Diagram

Ledinaire SlimDownlight



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, May 12 - data subject to change