Product Data Sheet

GW70004

70 RT HP Range





70 RT HP is a new range of 16A to 160A switch disconnectors in isolating material and metal, supplied in a box. Available in control and emergency versions, the range is completed by board versions for front-panel or DIN rail assembly, in 16 to 63A options, all of which can be equipped with auxiliary contacts. These devices have been designed for deliver the ultimate in reliability, functionality and performance. They offer a technologically advanced solution that simplifies installation, reduces wiring times and ensures maximum safety and robustness, even in the most demanding conditions, thanks to the use of high-performance materials.

Regulation field	87 - 145 mm	Rated current (A)	32
No. of poles	2P	No. of modules EN 50022	4
Knob colour	Red	Version	From board
Electrocod	1742	Lockable	Yes

BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS												
Saline solution	Acids		Bases		Solvents				Mineral	UV		
	Concentrated	Diluited	Concentrated	Diluited	Hexane	Benzol	Acetone	Ethyl alcohol	oil	rays		
Resistant	L <mark>imite</mark> d resistance	Resistant	Not resistant	L <mark>imite</mark> d resistance	L <mark>imite</mark> d resistance	Not resistant	Not resistant	L <mark>imite</mark> d resistance	Resistant	Resistant		

DIMENSIONAL





TECHNICAL SYMBOLOGY STANDARDS/APPROVALS

