

## PRODUCT DATASHEET DALI SENSOR LS/PD LI G2

DALI SENSOR LS/PD LI G2 | DALI-2 light and presence sensor, luminaire installation



### Areas of application

- Suitable for indoor applications
- Installation in office luminaires
- Suitable for floor standing luminaires in combination with an application controller
- Ceiling installation via LS/PD CI KIT or LS/PD AP KIT possible

### Product benefits

- Small housing design
- Frames for different mounting types for luminaires
- DALI-2 certified
- DALI Bus powered (No mains connection necessary)
- Multiple sensors connectable to the same DALI line
- Presence detection angle adjustable between 40...90° via integrated shutters
- Integretable in light- and building management systems supporting DALI-2 sensors

### Product features

- Light and presence sensor for luminaire installation
- Presence detection via passive IR element
- Light sensor operating range: 20...800 lx (measured at sensor)
- Mounting height: 2...5 m
- Function indicator with two-color LED

## TECHNICAL DATA

### Electrical data

Nominal wattage	0.10 W
Nominal voltage	16 V
Mains frequency	0 Hz

### Dimensions & Weight



Length	48.00 mm
Width	15.00 mm
Height	17.00 mm
Product weight	10.00 g

### Colors & materials

Product color	Light grey
---------------	------------

### Temperatures & operating conditions

Ambient temperature range	-20...+50 °C
---------------------------	--------------

### Capabilities

Dimmable	No
Dimming interface	DALI-2
Maximum installation height	5 m
Detection area	6 m
Detection angle	80 °
Type of installation	Ceiling integration/Luminaire integration
Operating range, light sensor	20...800 lx





### Certificates & Standards

Approval marks – approval	CE
Protection class	II
Type of protection	IP20

## EQUIPMENT / ACCESSORIES

– Attachable mounting frame for luminaire mounting from inside and outside

### DOWNLOAD DATA


Documents and certificates	
	User instruction
	Declarations Of Conformity CE
CAD/BIM files	
	CAD_STEP_3D
	CAD data 3D PDF

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4062172072069	Folding box 1	128 mm x 37 mm x 27 mm	49.00 g	0.13 dm <sup>3</sup>
4062172072076	Shipping box 25	223 mm x 197 mm x 179 mm	1131.00 g	7.86 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### ADDITIONAL CATALOG INFORMATION



### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.