PHILIPS Lighting



MASTER LEDspot ExpertColor AR111

MAS LEDExpertColor 20-100W 930 AR111 24D

MASTER LEDspot LV ExpertColor creates a warm and comfortable ambience for hospitality venues, homes and restaurants. It creates such an ambience with superior lighting that has a customized spectrum, high CRI, and deep dimming feature. The result? A beautiful lighting experience. What's more, the innovative, trimless lens design will suit almost any interior decor with its clean and neat look. In addition, you can take advantage of the full ExpertColor family, which also includes LEDspot MV and LEDspot Par lamps.

Product data

| General Information | |
|------------------------------------|--------------------|
| Cap-Base | G53 [G53] |
| EU RoHS compliant | Yes |
| Nominal lifetime | 40,000 hour(s) |
| Switching Cycle | 50,000 |
| Lighting Technology | LED |
| Flux measurement reference | Narrow Cone |
| Brand | Philips |
| | |
| Light Technical | |
| Color Code | 930 [CCT of 3000K] |
| Beam Angle (Nom) | 24 degree(s) |
| Luminous Flux | 1,270 lumen |
| Luminous Intensity (Nom) | 4,200 cd |
| Color Designation | White (WH) |
| Correlated Color Temperature (Nom) | 3000 K |
| Luminous Efficacy (rated) (Nom) | 63 lm/W |
| Color Consistency | <4 |
| | |


| Color rendering index (CRI) | 95 |
|---------------------------------------|-----------------|
| LLMF At End Of Nominal Lifetime (Nom) | 70 % |
| Luminous Flux in 90° Cone (Rated) | 1,270 lumen |
| | |
| Operating and Electrical | |
| Line Frequency | 50 to 60 Hz |
| Input Frequency | 50 to 60 Hz |
| Power Consumption | 20 W |
| Lamp Current (Nom) | 2,000 mA |
| Wattage Equivalent | 100 W |
| Starting Time (Nom) | 0.5 s |
| Warm-up time to 60% light | 0.5 s |
| Power Factor (Fraction) | 0.7 |
| Voltage (Nom) | 12 V |
| Voltage (Nom) | 12 V |
| | |
| Temperature | |
| Ambient temperature range | -20 °C to 45 °C |
| | |

MASTER LEDspot ExpertColor AR111

| T-Case Maximum (Nom) | 77 °C | |
|-------------------------------|----------------------------|--|
| | | |
| Controls and Dimming | | |
| Dimmable | Only with specific dimmers | |
| | | |
| Mechanical and Housing | | |
| Bulb Finish | Clear | |
| Bulb Shape | AR111 | |
| | | |
| Approval and Application | | |
| Suitable For Accent Lighting | Yes | |
| Energy Consumption kWh/1000 h | 20 kWh | |
| EPREL Registration Number | 1,122,533 | |


| Product Data | | |
|---------------------------------|--|--|
| Full product code | 871951442969700 | |
| Order product name | MAS LEDExpertColor 20-100W 930 AR111 24 | |
| Order code | 929003478702 | |
| Numerator - Quantity Per Pack | 1 | |
| Numerator - Packs per outer box | 6 | |
| Material number (12NC) | 929003478702 | |
| Net weight | 0.162 kg | |
| Full product name | MAS LEDExpertColor 20-100W 930 AR111 24D | |
| EAN/UPC - Case | 8719514429703 | |
| | | |

Dimensional drawing




| Product | D | С |
|--|--------|-------|
| MAS LEDExpertColor 20-100W 930 AR111 24D | 111 mm | 62 mm |

Photometric data




Spectral Power Distribution Colour - MAS LEDExpertColor 20-100W 930 AR111 24D




Light Distribution Diagram - MAS LEDExpertColor 20-100W 930 AR111 24D

MASTER LEDspot ExpertColor AR111


Photometric data



Lifetime



Life Expectancy Diagram - MAS LEDExpertColor 20-100W 930 AR111 24D



Lumen Maintenance Diagram - MAS LEDExpertColor 20-100W 930 AR111 24D



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, April 17 - data subject to change