INE'S'A

50 W

50,0 W

220-240V

50/60 Hz

250 mA

0.90

PRODUCT INFORMATION

Product code
Product code (long)
Product description
EAN code
Category

PHOTOMETRIC DATA

PHOTOMETRIC DATA		MECHANICAL DATA	
Nominal luminous flux	5000 lm	Overall length	1275 mm
Rated luminous flux	5000 lm	Overall width	112 mm
Nominal beam angle (half-peak value)	110°	Overall height	89 mm
Rated beam angle (half-peak value)	100°	Weight	4,000 kg
Correlated colour temperature	4000K		
Colour temperature designation	Neutral White		
Colour consistency	3 SDCM		
Warm-up time to reach 60% of full light	1 s		

LIFE SPAN

Nominal life time	500
Rated life time	500
Number of switching cycles	250
Lumen main.fact.at end of nom.life time	0,7
Warranty	3 ye

50000h

50000h 25000

3 years

60340

IE-TP-CYVT-50-5000-4000K

CYVT Triproof 50W 5klm

5999097603407

Tri Proof Light

ADDITIONAL TECHNICAL INFORMATION

ELECTRICAL DATA

Nominal wattage

Rated wattage

Nominal voltage

Nominal current Power factor

Operating frequency

Starting time	1,0 s
Optimum operating ambient temperature	-20°C~40°C
Dimming	non-dimmable
Energy consumption	50 kW/1000h
IP rating	IP66
IK rating	IK07

