
# **ZONO PRO** 582074.004.76 | Wall luminaires





Wall luminaires 4051859753681 L 100, B 154, H 127

Wall (surface) silver, matt (approx. RAL 9006)



Wallscaping: elegant and innovative wall luminaire for accent lighting. Housing made of corrosion-resistant die-cast aluminium, seawater resistant powder-coated. With membrane valve as a standard to avoid condensed water. Cover made of ceramic-coated toughened glass with bayonet lock. COB LED with socket for easy replacement. Light emission: down. with rotationally symmetrical reflector. Fixing on the wall outside the sealed volume, drill hole deviations can be compensated. Screwless luminaire fixing via RZB Gravolock® System. Electrical plug and play featuring quick connector. Cable entry granting two cables for loop-through. Driver integrated. Dimmable DALI..

**Product specifications** 

Product specifications	
Length L	100 mm
Width B	154 mm
Height H	127 mm
Weight	2 kg
Light source	LED
Colour temperature	3000 K
Rated luminous flux	1150 lm
System power	12 W
System efficiency	96 lm/W
Glare evaluation UGR (4H 8H)	16,7
Beam angle	37°
Rated life	50000 h (L80/B10)
Colour rendering index (CRI)	80
Colour tolerance	3
Photobiological safety according to EN 62471	Risk group 1
Driver	Converter, dimmable
Control	DALI
Voltage	220 - 240 V / 50 Hz, 60 Hz
Luminaires on B10A fuse	31
Luminaires on B16A fuse	50
Luminaires on C10A fuse	52
Luminaires on C16A fuse	85
Inrush current / Inrush current duration	5 A / 50 μs
CIE Flux Code / CEN Flux Code	98 100 100 100 100
Type of protection	IP 65
Protection class	1
Filament test	960 °C
Impact resistance	IK07
Ambient temperature	-20 °C + 35 °C
Conformity mark	CE

## **ZONO PRO**

#### 582074.004.76 | Wall luminaires



#### **Accessories**



982769.003 Safety glass. Blanking cover.



982769.033 Safety glass. Centre: transparent with pressed glass lens Superspot.



982769.053 Safety glass. Centre: transparent d 50 mm. For reflectors, Spot and Flood.



982846.004 Reflector spot



982846.014 Reflector flood

### **Spareparts**



982769.053 Safety glass. Centre: transparent d 50 mm. For reflectors, Spot and Flood.



982846.014 Reflector flood