

PRODUCT DATASHEET Bathroom Wall 455mm E14 Black

Bathroom Wall Luminaire IP44 E14 | Luminaire with socketed base and IP44



Areas of application

- Indoor applications
- Bathrooms (IP44)

Product benefits

- Socketed luminaire, the lamps can be replaced

Product features

- Type of protection: IP44
- The cover is made of high quality glass



TECHNICAL DATA

Electrical data

Nominal voltage	220240 V
Mains frequency	5060 Hz
Protection class	1
Operating mode	Mains voltage

Dimensions & Weight

Length	86.00 mm
Width	72.00 mm
Height	455.00 mm
Product weight	1442.00 g

BATH CLASSIC CYLINDERW45CMIP44E14

Materials & Colors

Product color	Black
Housing color	Black
Body material	Steel
Cover material	Glass
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20+40 °C
Temperature range at storage	-20+80 °C
Type of connection	Screw terminal, 3-Pole
Type of protection	IP44
Dimmable	No
Mounting type	Surface
Application environment	Indoor
With light source	No

Holder designation	E14

Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No

Additional product data

Product remark	Maximum bulb wattage: 3 x 12 W LED
Number of illuminants	3

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.

DOWNLOAD DATA

	Documents and certificates Document name		
User instruction / safety instructions		UI BATHROOM CLASSIC CYLINDER	
PDF	Legal information	Legal Insert	
PDF	Declarations of conformity	CE Declaration Bathroom Classic	
PDF	Declarations of conformity UKCA	UKCA Declaration Bathroom Classic	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854103292	Folding box 1	90 mm x 180 mm x 475 mm	2108.00 g	7.70 dm ³
4099854103308	Shipping box 4	380 mm x 200 mm x 505 mm	9014.00 g	38.38 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.