

# SLI035056NW\_PW\_CN\_3H\_A

SLI035056NW\_PW\_CN\_3H\_A

---



---

Power	<b>40 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>5500 lm (360°)</b>	Colour temperature	<b>4000 K</b>
Colour of light	<b>Neutral white</b>	Beam angle	<b>120 °</b>
Degree of protection (IP)	<b>IP20</b>		

---

## Technical data

---

Code	SLI035056NW_PW_CN_3H_A
Power	40 W
Nominal current	186 mA
Voltage	230 V
Energy consumption	40 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.9
Useful luminous flux*	5500 lm (360°)
Luminous flux**	4800 lm (360°)
Lamp efficacy	138 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	120 °
RA	>80
Uniformity of color SDCM max	5
Dimmable	OPC
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum/Plastic
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	595x595x26 mm
Mounting hole	575x575mm mm
For use	Inside
Assembly method	Recessed
Application	INT
Made in	PRC