

PRODUCT DATASHEET

NIGHTLUX Torch White

NIGHTLUX® Torch | Nightlights with motion sensor and torch function, battery-powered



Areas of application

- For a very large range of uses
- Indoor and outdoor
- Ideal for the home or on the move

Product benefits

- Attractive and functional design
- Economical operation due to low power consumption
- Easy and fast mounting on nearly every surface (adhesive tape or screws)
- Accessories for flexible mounting options included
- Can be removed from the holder for use as a portable light

Product features

- Integrated light and motion sensor
- Available in two housing colors
- Switch for Auto- or On/Off-Mode
- Type of protection: IP54



TECHNICAL DATA

Electrical data


| | |
|---|-----------|
| Nominal wattage | 0.35 W |
| Nominal voltage | 4,5 V |
| Mains frequency | 0 Hz |
| Nominal current | 77.000 mA |
| Max. number of luminaires per miniature circuit breaker C10 | - |
| Protection class | III |
| Operating mode | Battery |

Photometrical data

| | |
|--------------------------------------|---------------------|
| Luminous flux | 10 lm |
| Color temperature | 4000 K |
| Light color (designation) | Cool White |
| Color rendering index Ra | > 80 |
| Standard deviation of color matching | ≤6 sdc _m |

Dimensions & Weight

| | |
|----------------|-----------|
| Length | 195.00 mm |
| Width | 140.00 mm |
| Height | 45.00 mm |
| Product weight | 95.00 g |



Materials & Colors

| | |
|---------------|-------|
| Product color | White |
| Housing color | White |

| | |
|-----------------|--------------------|
| Body material | Polycarbonate (PC) |
| Mercury content | 0.0 mg |

Application & Mounting

| | |
|------------------------------|-----------------|
| Ambient temperature range | 0...+25 °C |
| Temperature range at storage | -20...+50 °C |
| Type of protection | IP54 |
| Dimmable | No |
| Mounting type | Surface |
| Mounting location | Wall |
| Application environment | Indoor |
| LED module replaceable | Not replaceable |
| With light source | Yes |

Lifespan

| | |
|---------------------------|-----------------------|
| Lifespan L70/B50 at 25 °C | 25000 h ¹⁾ |
|---------------------------|-----------------------|

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Sensor

| | |
|-------------------|------------------------|
| Type of sensor | Light / Motion |
| Sensor technology | Passive infrared (PIR) |

BATTERY

| | |
|------------------------------|----------|
| Type of Battery | Alkaline |
| Battery size [GMS] | AAA |
| Number of included batteries | 3 |
| Nominal voltage of battery | 1.5 V |

Certificates & Standards

| | |
|-----------|-----------------|
| Standards | CE / EAC / UKCA |
|-----------|-----------------|

EQUIPMENT / ACCESSORIES

– Batteries included: 3x1.5 V LR03 (AAA)

DOWNLOAD DATA

Documents and certificates



Declarations Of Conformity CE

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075260696 | Blister 1 | 45 mm x 140 mm x 195 mm | 116.00 g | 1.23 dm ³ |
| 4058075260702 | Shipping box 6 | 300 mm x 154 mm x 210 mm | 812.00 g | 9.70 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.