

# LED CANDLE

WOJ+14646

Dimmable LED source LED CANDLE 5,5 W with E-14 base and in the shape of a glass 'candle'. It is characterised by a high light efficacy 145 lm/W. Compatible with popular wall dimmers\*. It is even more energy-efficient thanks to the use of durable COG filaments, which consume very little electricity. Wide beam angle 300° ensures even illumination of the room. \*Recommended dimmers: Berker 2867 10, Schneider SBD600RL, Simon S9L, Simon S9T, V-PRO.



Power	<b>5,5 W</b>	Voltage	<b>230 V</b>
Luminous flux**	<b>800 lm (360°)</b>	Colour temperature	<b>2700 K</b>
Colour of light	<b>WW</b>	Beam angle	<b>300 °</b>
Socket	<b>E14</b>		

## Technical data

---

Code	WOJ+14546
Power	5,5 W
Nominal current	34 mA
Voltage	230 V
Energy efficiency class	D
Energy consumption	6 kWh/1000h
Frequency	50HZ Hz
Power factor	0.7
Useful luminous flux*	800 lm (360°)
Luminous flux**	800 lm (360°)
Lamp efficacy	145 lm/W
Colour temperature	2700 K
Colour of light	WW
Beam angle	300 °
RA	80
Uniformity of color SDCM max	5
Dimmable	Yes
Working temperature range	-20/+40 °
Lifespan	17000 h
Socket	E14
Dimension (AxBxC)	35x98 mm
For use	Inside
Application	INT
Made in	PRC
Other	WOJ+06586; Berker 2867 10, 2973; ,

## Related documents

---



 Declaration of Conformity

