



MASTER PL-C 2 Pin

MASTER PL-C 18W/840/2P 1CT/5X10BOX

MASTER PL-C is an efficient medium-wattage compact fluorescent lamp, typically used in general downlights for retail, hospitality and office applications. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 2-pin version is designed for operation on electromagnetic gear and is provided with a plug-in/pull-out lamp base.

Warnings and Safety

- \cdot Use only with electromagnetic control gear
- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position
- Dimming is not possible
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

| Color rendering index (CRI) | 80 | | |
|-----------------------------|---------|--|--|
| | | | |
| Operating and Electrical | | | |
| Power Consumption | 18.3 W | | |
| Lamp Current (Nom) | 0.230 A | | |
| | | | |
| Controls and Dimming | | | |
| Dimmable | No | | |
| | | | |
| Approval and Application | | | |
| Mercury (Hg) Content (Max) | 1.4 mg | | |
| Mercury (Hg) Content (Nom) | 1.4 mg | | |
| | | | |


Datasheet, 2023, May 16 data subject to change

MASTER PL-C 2 Pin

| Energy Consumption kWh/1000 h | 19 kWh | | | | |
|-------------------------------|------------------------------------|--|--|--|--|
| EPREL Registration Number | 423,284 | | | | |
| | | | | | |
| Product Data | | | | | |
| Full product code | 871150062093470 | | | | |
| Order product name | MASTER PL-C 18W/840/2P 1CT/5X10BOX | | | | |
| Order code | 927905784040 | | | | |


| Numerator - Quantity Per Pack | 1 50 927905784040 MASTER PL-C 18W/840/2P 1CT/5X10BOX | | | |
|---------------------------------|---|--|--|--|
| Numerator - Packs per outer box | | | | |
| Material number (12NC) | | | | |
| Full product name | | | | |
| EAN/UPC - Case | 8711500715784 | | | |
| | | | | |

Dimensional drawing




| Product | D (max) | D1 (max) | A (max) | B (max) | C (max) |
|-----------------------------|---------|----------|----------|----------|----------|
| MASTER PL-C 18W/840/2P 1CT/ | 27.1 mm | 27.1 mm | 109.5 mm | 128.0 mm | 150.4 mm |
| 5X10BOX | | | | | |

Photometric data



Spectral Power Distribution Colour - MASTER PL-C 18W/840/2P 1CT/5X10BOX

Lifetime






Life Expectancy Diagram - MASTER PL-C 18W/840/2P 1CT/5X10BOX

Life Expectancy Diagram - MASTER PL-C 18W/840/2P 1CT/5X10BOX

MASTER PL-C 2 Pin

Lifetime



Lumen Maintenance Diagram - MASTER PL-C 18W/840/2P 1CT/5X10BOX



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.