

PRODUCT DATASHEET CONVERSION KIT + LED TUBE T8 EM P 1500 mm 20W 865

LED TUBE T8 EM P CONVERSION KIT | LED tubes for electromagnetic control gear (CCG), including conversion kit for double lamp luminaires



Areas of application

- General illumination within ambient temperatures from -20...+50 °C
- Illumination of production areas
- Traffic zones and corridors
- Supermarkets and department stores
- Industry

Product benefits

- Only around 5 minutes per luminaire needed for rewiring
- No ECG compatibility issues
- No ECG maintenance necessary
- No bending thanks to glass tube
- Energy savings of up to 66 % (compared to T8 fluorescent lamp)
- Instant-on light, therefore ideally suitable in combination with sensor technology
- Very high resistance to switching loads
- Also suitable for operation at low temperatures

Product features

- Contains 10 LED TUBE T8 EM P LED tubes and 5 conversion kits for double-lamp luminaires
- Conversion kit contains all necessary material for conversion of ECG luminaires to AC mains



October 11, 2023, 07:22:39 CONVERSION KIT + LED TUBE T8 EM P 1500 mm 20W 865

- Detailed step-by-step instruction for guaranteed TÜV-certification available
- LED replacement for classic T8 fluorescent lamps with G13 socket for use in CCG luminaires or on AC mains
- Low flicker according to EU 2019-2020 (SVM \leq 0,4 / PstLM \leq 1)
- Single and tandem operation on conventional control gear (0.6 m version)
- Lamp tube made of glass with splinter protection e.g. for food industry applications
- Mercury-free and RoHS compliant
- Uniform illumination
- Type of protection: IP20

TECHNICAL DATA

Electrical data

Nominal wattage	20 W
Nominal voltage	220240 V
Nominal current	90 mA

Photometrical data

Luminous flux	3100 lm
Luminous efficacy	155 lm/W
Light color	865

Light technical data

Dimensions & Weight

Product weight 2283.00 g

Additional product data

	This product contains the following LED Tube as a light source: LED	
Product remark	TUBE T8 EM P 1500 mm 20W 865, EAN: 4099854037153, LED tube	
	EEC: D	

Certificates & Standards

Type of protection	IP20
--------------------	------

Country-specific categorizations

Order reference	LEDTUBE T8 EM P
Order reference	

Safety advice

- Not suitable for operation with electronic control gear.

- Operation in outdoor applications in suitable damp-proof luminaires possible according to data sheet and installation instruction.

- Not suitable for emergency lighting

DOWNLOAD DATA

Documents and certificates

PDF

Installation guide

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854108204	Shipping box 1	1,635 mm x 180 mm x 95 mm	3457.00 g	27.96 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For current information see www.ledvance.com/ledtube

Legal advice

- When used to replace a T8 fluorescent lamp the total energy efficiency and light distribution depends on the design of the lighting system.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.