Product End-of-Life Instructions

KNX Lead gel Batteries







Product End-of-Life Instructions - EoLI

Product overview

Product Range: KNX Lead gel Battery 18 Ah

Marketing Model/Name: MTN668991 / KNX Lead gel Battery 18 Ah

SiZe: $H \times L \times D$ in mm = 181 x 76 x 167

Weight in g with Battery = 5850 grams

Weight in g without Battery = 250 grams

Purpose

The product family must be disposed according to the legislation of the country. This document is intended for use by end of life recyclers or treatment facilities. It provides the basic information to assure an appropriate end of life treatment for the components and materials of the product.

Note:

This product family is not in the scope of EU directive 2002/96/EC, Waste Electrical and Electronic Equipment (WEEE). It's under the Battery Directive.

Operations recommended for the end of life treatment

There are several steps to process the products at the end of life so as to recover components, materials or energy:

Reuse → Separation for special treament → Depollution → Dismantling → Shredding

The components of the products that optimize the recycling performances are listed, identified and located hereunder.

Product End-of-Life Instructions – EoLI



Number on drawing	Components	Weight (in g)	Comment
Components listed for Operating Hazards			
	Lead	2500 g	
	Lead Dioxide	1400 g	
	Sulfuric Acid Electrolyte	1250 g	
Components listed for Shredding			
	Plastic Parts	150 g	
	Metal Parts	200 g	
	Glass	100 g	

EoLl achieved with Schneider-Electric TT03 V5 procedure

Schneider Electric Industries SAS 35, rue Joseph Monier CS 30323 F- 92506 Rueil Malmaison Cedex RCS Nanterre 954 503 439 Capital social 896 313 776 €

www.schneider-electric.com

© 2014 - Schneider Electric - All rights reserved