

Permanent Light 216 / Bulb

Bulb 7W BA15D 12V



Part No.: 955.015.34

| MECHANICAL DATA | | |
|-----------------------|--------|--|
| Height | 54 mm | |
| Diameter | 16 mm | |
| Housing colour | Silver | |
| Weight with packaging | 10 g | |
| Product weight | 8 g | |

| ELECTRICAL DATA | | |
|-----------------------------|----------|--|
| Operating voltage | 12V | |
| Operating voltage frequency | 50Hz | |
| Operating voltage tolerance | +/- 10% | |
| Rated operational voltage | 12 VDC | |
| Rated operational current | 583 mA | |
| Rated inrush current | 5.830 mA | |
| Power illuminant | 7 W | |

| OPTICAL DATA | |
|---------------------|-------|
| Lamp fitting/socket | BA15d |

| APPROVAL DATA | |
|------------------------------|--------------------------------|
| Conforms with CE | No |
| Conforms with RoHS directive | Fulfills substance restriction |
| WEEE | No |
| Conforms with ATEX-directive | No |
| Conforms with CCC | No |
| Conforms with FCC | No |
| Conforms with IC | No |
| EAC certificate available | No |
| Conforms with AS-I | No |
| ICAO Certification | No |
| Conforms with DNV | No |
| Conforms with RoHS CN | No |

For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.