



product description: The anchor is suitable for offset, slide and distance assembly. Approved for concrete C20/25 - C50/60, with both pulled and compressed zones. Also suitable for natural stone with solid structure, concrete C12/15 and C80/95

surface finish: PO - bichromatic galvanised

sales amount: á 1 pc

classification: ČSN 73 0895 P 90-R  
 DIN 4102-12 E 90  
 STN 92 0205 PS 90

Fire classification is depend on the specific conditions of the cable tray, detailed in the catalog Systems with maintained functionality in fire.

storage: EN 60721-3-1

item number	seismic-approval	drill hole Ø A (mm)	anchor length B (mm)	min. drill hole depth for through fixings C (mm)	max. usable length D (mm)	thread (mm)
<b>KPO 6X70_PO</b>	-	6	65	60	10	M 6 x 25
<b>KPO 8X77_PO</b>	<b>C1</b>	8	75	65	10	M 8 x 38
<b>KPO 8X97_PO</b>	<b>C1</b>	8	95	85	30	M 8 x 58
<b>KPO 8X110_PO</b>	<b>C1</b>	8	115	105	50	M 8 x 78
<b>KPO 10X95_PO</b>	<b>C1/C2</b>	10	95	85	10	M 10 x 53
<b>KPO 10X115_PO</b>	<b>C1/C2</b>	10	115	105	30	M 10 x 73
<b>KPO 10X175_PO</b>	<b>C1/C2</b>	10	185	175	100	M 10 x 143
<b>KPO 12X120_PO</b>	<b>C1/C2</b>	12	110	100	10	M 12 x 61