



LED luminaire MONA 4, with a power of 27 W. It is made of high-quality components, supported by a 5-year warranty. It also stands out for its very high colour rendering index RA>95. Narrow beam angle 60° gives directional light so that selected objects or surfaces can be better exposed. Designed for recessed mounting.





Power27 WVoltage230 VColour of lightBREADBeam angle60 °Degree of protection (IP)IP20IP20IP20

www.spectrumled.pl



Technical data

Oodo	W0JP05514
Code Power	27 W
Nominal current	27 W 129 mA
Voltage	230 V
Energy consumption	27 kWh/1000h
Frequency	50HZ Hz
Protection class	Ш
Power supply included	+
Manufacturer of power	TCI
supply Power factor	0.93
Useful luminous flux*	
USEIUI IUITIITUUS IIUX**	2565 lm (360°)
Editinious have	2295 lm (360°)
Lamp efficacy	95 lm/W
Colour of light	BREAD
Beam angle	60 °
RA	95
Light source included	+
Producer of LED diodes	CITIZEN
Uniformity of color SDCM max	3
Dimmable	OPC
Working temperature range	-20/+40°
Lifespan	50000 h
Housing material	Aluminum
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	193x130 mm
Mounting hole	0160 mm
For use	Inside
Assembly method	Recessed
Application	Inside
Made in	PL

