



Leo Polycarbonate Bollard Connected by WiZ



Voice Control

- Modern styled WiZ embedded bollard with polycarbonate construction suitable for residential and hospitality applications
- White reflector with clear polycarbonate diffuser
- Polycarbonate construction is ideal for coastal applications
- Supplied c/w root mounting kit, can be surface mounted with rawbolts
- Tunable between 2700K - 6500K via WiZ App and voice control



OCTO
Embedded

Connected by

WiZ



INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	SDCM	BEAM ANGLE	CLASS	IP	IK
230V	50/60Hz	-10°C to 40°C	L70 36,000	Ra 80	6	130°	1	IP65	08

CODE	DESCRIPTION	WATTAGE	CCT	LUMENS	LM/W	A	TRADE
ALEOLED/045/GR/OCTOW	Tunable White - 450mm	9W	2700K-6500K	560lm (2700K) - 572lm (6500K)	61lm (2700K) - 64lm (6500K)	450mm	£200.00
ALEOLED/075/GR/OCTOW	Tunable White - 750mm	11W		836lm (2700K) - 852lm (6500K)	69lm (2700K) - 77lm (6500K)	750mm	£234.00
ALEOLED/100/GR/OCTOW	Tunable White - 1000mm			1000mm	£258.00		

