



## AK ZS 8.10 FL30 GBM10X60 V4A (478 129)



Figure without obligation



| Type  | AK ZS 8.10 FL30 GBM10X60 V4A |
|---|------------------------------|
| Part No.  | 478 129                      |
| Material of clamp                                     | StSt (V4A)                   |
| Clamping range Rd / FI                                | 8-10 / 30 mm                 |
| Material of bolt                                      | StSt (V4A)                   |
| Screw   | M10 x 60 / M8 x 16 mm        |
| Material of screw / nut                               | StSt (V4A)                   |
| Material No.  | 1.4571 / 1.4404 / 1.4401     |
| Dimensions  | 58 x 30 x 2.5 mm             |
| Lightning current carrying capability (10/350 µs)     | <sup>*)</sup>                |
| Standard  | EN 62561-1                   |
| Short-circuit current (AC 50 Hz / DC) (1 s; ≤ 300 °C) | 2.7 kA                       |
| Weight  | 140 g                        |
| Customs tariff number                                 | 85389099                     |
| GTIN  | 4013364118508                |
| PU  | 10 Stk                       |

<sup>\*)</sup> For exact assignment see test certificate.

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.