

# FIALE 3 STEPS

SLI022026WW\_PW

Recessed lighting luminaire FIALE 3 STEPS, with a power of 12,5 W, high light efficacy 120 lm/W. The luminaire has three lighting modes: each on/off will change the mode. It shines with a warm light (3000K), which promotes relaxation and rest, making the illuminated room cosier. Designed for recessed mounting.



---

Power	<b>12,5 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>1500 lm (360°)</b>	Colour temperature	<b>3000 K</b>
Colour of light	<b>WW</b>	Beam angle	<b>120 °</b>
Degree of protection (IP)	<b>IP20</b>		

---

## Technical data


---

Code	SLI022026WW_PW
Power	12,5 W
Nominal current	75 mA
Voltage	230 V
Energy consumption	13 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power factor	0,5
Useful luminous flux*	1500 lm (360°)
Luminous flux**	1000 lm (360°)
Lamp efficacy	120 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	120 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	PLASTIC
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	148x37 mm
Mounting hole	128 mm
For use	Inside
Assembly method	Recessed
Application	INT
Made in	PRC


## Related documents

---



 User manual



 Declaration of Conformity

