

SLI033032CCT_PW

SLI033032CCT_PW




Power	20 W	Voltage	230 V
Luminous flux*	2225 lm (360°)	Colour temperature	3000/4000/6000 K
Colour of light	CCT	Beam angle	20-45 °
Degree of protection (IP)	IP20		

Technical data


Code	SLI033032CCT_PW
Power	20 W
Nominal current	145 mA
Voltage	230 V
Energy consumption	20 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	Yes
Power factor	0,5
Useful luminous flux*	2225 lm (360°)
Luminous flux**	1700 lm (360°)
Lamp efficacy	111 lm/W
Luminous intensity	3100 cd
Colour temperature	3000/4000/6000 K
Colour of light	CCT
Beam angle	20-45 °
RA	80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, PLASTIC
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	84x136x185 mm
For use	Inside
Assembly method	on track
Application	Inside
Made in	PRC
Other	Light color change function 3000K/4000K/6000K ,

Related documents



 User manual



 Declaration of Conformity