

PRODUCT DATASHEET FLASHLIGHT CAR EMERGENCY

FLASHLIGHT CAR EMERGENCY | Outdoor mobiles



- Multifunctional



Product benefits

- 4 operating modes: 1 press: bright light 100 lm, 2nd press: soft light 70 lm, 3rd press: SOS mode, 4th pressing: flashing mode
- The angle of the light beam is adjusted by turning the lens
- 1,5 h of running at full brightness
- Powered by 4 AAA batteries (not included)

Product features

- Glass hammer, seat belt knife
- Sturdy aluminum housing
- Convenient button for switching modes

TECHNICAL DATA

Electrical data

| Nominal wattage | 1.60 W |
|--------------------------------------|---------|
| Inrush current | 270 mA |
| Inrush current time T _{h50} | 0.5 s |
| Operating mode | Battery |

Photometrical data

| Luminous flux | 100 lm |
|---------------------------|------------|
| Luminous efficacy | 62 lm/W |
| Color temperature | 6500 K |
| Light color (designation) | Cool White |
| Color rendering index Ra | 70 |

Dimensions & Weight

| | Diameter | 34.00 mm |
|---|----------------|-----------|
| Ī | Height | 416.00 mm |
| | Product weight | 320.00 g |

Materials & Colors

| Product color | Black |
|-----------------|----------|
| Housing color | Black |
| Body material | Aluminum |
| Mercury content | 0.0 mg |

Application & Mounting

| Ambient temperature range | -20+40 °C |
|---------------------------|-----------|
| Dimmable | No |
| Adjustable | No |
| With light source | Yes |

Lifespan

| Lifespan L70/B50 at 25 °C | 30000 h 1) |
|---------------------------|------------|
|---------------------------|------------|

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

| Standards | CE / UKCA |
|----------------------------------|-----------------|
| Replaceable light source (EPREL) | Not replaceable |

DOWNLOAD DATA

| | Documents and certificates | Document name | |
|-----|----------------------------|------------------------------------|--|
| PDF | Legal information | Informationstext 18 Abs 4 ElektroG | |
| PDF | Declarations of conformity | CE Declaration Flashlight | |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4099854175824 | Folding box | 43 mm x 43 mm x 426 mm | 356.00 g | 0.79 dm ³ |
| 4099854175831 | Shipping box 24 | 271 mm x 189 mm x 455 mm | 8986.00 g | 23.30 dm ³ |
| 4099854583995 | Shipping box 8 | 490 mm x 300 mm x 165 mm | 3504.00 g | 24.26 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.