


PRODUCT-DETAILS

# S403M-B8NP

## S403M-B8NP Miniature Circuit Breaker



### General Information

Extended Product Type	S403M-B8NP
Product ID	2CCS573103R8085
EAN	7612270108510
Catalog Description	S403M-B8NP Miniature Circuit Breaker
Long Description	<p>SMISSLINE TP S400M are a current limiting miniature circuit breakers. They have two different tripping mechanisms, the delayed thermal tripping mechanism for overload protection and the electromechanic tripping mechanism for short circuit protection. They are available in different characteristics (B,C,D,K), configurations (1P,1P+N,2P,3P,3P+N), breaking capacities (up to 10 kA at 240/415 V AC ) and rated currents (up to 63A). MCBs of the product range S400M are comply with IEC/EN 60898-1 for B,C and D characteristic and IEC/EN 60947-2 for C and K characteristic. The pluggable solution is only for the SMISSLINE TP System, allowing the use for commercial, industrial, and critical power applications.</p>

### Technical

Standards	IEC/EN 60898-1
Tripping Characteristic	B
Rated Operational Voltage	acc. to IEC 60898-1 230 ... 400 V AC
Operational Voltage	Minimum 12 V AC
Rated Insulation Voltage (U <sub>i</sub> )	acc. to IEC/EN 60664-1 440 V
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	4 kV

Input Voltage Type	AC
Rated Current ( $I_n$ )	8 A
Rated Operational Current ( $I_e$ )	8 A
Rated Short-Circuit Capacity	(AC) 10 kA (230 V AC) 10 kA (230 / 400 V AC) 10 kA
Frequency (f)	50 ... 60 Hz
Rated Frequency (f)	50 ... 60 Hz
Power Loss	5.6 W
Power Supply Connection	Arbitrary
Contact Position Indication	Red ON / Green OFF
Energy Limiting Class	3
Electrical Endurance	10000 cycle
Mechanical Endurance	10000 cycle
Number of Poles	4
Number of Protected Poles	4
Overvoltage Category	III
Tightening Torque	2.8 N·m
Release Type	B
Screw Terminal Type	Failsafe Bi-directional Cylinder-lift Terminal
Actuator Marking	I / O
Mounting Position	Any
Recommended Screw Driver	Pozidriv 2
Accessories Available	Yes
Connecting Capacity	Flexible with Ferrule 0.75 ... 25 mm <sup>2</sup> Flexible 0.75 ... 25 mm <sup>2</sup> Rigid 0.75 ... 35 mm <sup>2</sup> Stranded 0.75 ... 35 mm <sup>2</sup>
Terminal Type	Screw Terminals

## Environmental

Ambient Air Temperature	Operation -25 ... +60 °C Storage -40 ... +70 °C
Reference Ambient Air Temperature	30 °C
Degree of Protection	IP20
Pollution Degree	3
Resistance to Vibrations acc. to IEC 60068-2-6	2...13.2 Hz/1 mm 13.2...100Hz/0.7 g, 5 cycles 5...150 ... 5 Hz/1 g, 4 waves
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Information	9AKK107991A9634
Environmental Information	9AKK108467A9561
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

## Dimensions

Width in Number of Modular Spacings	4
-------------------------------------	---

Product Net Width	72 mm
Product Net Height	91 mm
Product Net Depth / Length	75 mm
Product Net Weight	428 g
Size	4 modules
Built-In Depth (t <sub>2</sub> )	75 mm
Dimension Diagram	9AKK107492A6192

---

## Ordering

Minimum Order Quantity	1 piece
Package Level 1 Units	carton 3 piece
Package Level 1 Gross Weight	1355 g
E-Number (Switzerland)	809077817

---

## Certificates and Declarations

Declaration of Conformity - CE	9AKK107991A9634
--------------------------------	-----------------

---

## Installation

Instructions and Manuals	2CCC451019M0109
--------------------------	-----------------

---

## Popular Downloads

Data Sheet, Technical Information	9AKK107492A6192
-----------------------------------	-----------------

---

## Classifications

ETIM 8	EC000042 - Miniature circuit breaker (MCB)
ETIM 9	EC000042 - Miniature circuit breaker (MCB)
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	85362020
eClass	V11.0 : 27141901
Object Classification Code	FC

---

## Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
2CCS500900R0081	HK40011-L	HK40011-L Auxiliary switch	1	piece
2CCF201112R0001	HK40020-L	HK40020-L Auxiliary switch	1	piece
2CCF201114R0001	HK40002-L	HK40002-L Auxiliary switch	1	piece
2CCS500900R0101	SK40011-L	SK40011-L Signal contact	1	piece
2CCF201162R0001	SK40020-L	SK40020-L Signal contact	1	piece
2CCF201164R0001	SK40002-L	SK40002-L Signal contact	1	piece
2CCS500900R0141	SK40010-LSA	SK40010-LSA Signal contact	1	piece
2CCF201212R0001	HK40010-LSA	HK400 10-L SA Auxiliary switch	1	piece
2CCS500900R0161	ZLS931	ZLS931 Spare parts	1	piece
2CCA880212R0001	CMS-122PS	CMS-122PS Sensor	3	piece
2CCA880102R0001	CMS-102PS	CMS-102PS Sensor	3	piece

## Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Plug-in Distribution Systems → Plug-in Distribution Systems → Miniature Circuit Breakers MCBs

