Product Information Sheet

dimensions

without

Width

Depth

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name	e or trade mark:	PHILIPS			
Supplier's addre	ess: Customer Ca	re Philips, I.B.R.S./C	.C.R.I. /Numéro 10461,	5600VB Eindhoven, NL	
Model identifie	r: 871150021393	38			
Type of light so	urce:				
Lighting technol	logy used:	МН	Non-directional or directional:	DLS	
Light source cap-type		GX8.5			
(or other electric interface)					
Mains or non-mains:		NMLS	Connected light source (CLS):	No	
Colour-tuneable	e light source:	No	Envelope:	Second	
High luminance	light source:	No			
Anti-glare shield	d:	Yes	Dimmable:	No	
		Product para	meters		
Parameter		Value	Parameter	Value	
		General product p	arameters:		
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		74	Energy efficiency class	G	
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		2 800 in Narrow cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 200	
On-mode power (P _{on}), expressed in W		73,2	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00	
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	96	
Outer	Height	95	Spectral power	See image	

111

111

distribution in the

in last page

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
· · · · · · · · · · · · · · · · · · ·		16				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity	0,371			
		coordinates (x and y)	0,366			
Parameters for directional light sources:						
Peak luminous intensity (cd)	14 300	Beam angle in degrees, or the range of beam angles that can be set	24			

(a)'-': not applicable; (b)'-': not applicable;

