



CoreLine Trunking Gen2

LL200Z MB-SW 2xEP CU9 WH

LL200Z | Coreline Trunking Gen2 - - - IP20 | Finger-protected - IK02 | 0.2 J standard - White

CoreLine Trunking Gen2 is a light-line system that is designed for simplicity. It comes in a choice of lengths, flux packages and beam shapes to suit every project and application. Easy to use and integrate with spots and sensors, CoreLine Trunking Gen2 provides consistent, high-quality lighting with added protection against accidental water ingress. The innovative system is also easy to assemble and install for faster retrofits and refurbishments.

Product data

General Information		Dimensions (Height x Width x Depth)	
Angle	-		50 x 80 x 267 mm
Accessory color	White	Material	Steel
Product family code	LL200Z [Coreline Trunking Gen2]	Approval and Application	
Value ladder	Value	Ingress protection code	IP20 [Finger-protected]
Operating and Electrical		Mech. impact protection code	IK02 [0.2 J standard]
Input Voltage	220 to 240 V	Protection class IEC	Safety class I
Line Frequency	50 to 60 Hz	Product Data	
Input Frequency	50 to 60 Hz	Full product code	871951410820200
Mechanical and Housing		Order product name	LL200Z MB-SW 2xEP CU9 WH
Overall length	267 mm	Order code	910925867563
Overall width	80 mm	Numerator - Quantity Per Pack	1
Overall height	50 mm	Numerator - Packs per outer box	1
		Material number (12NC)	910925867563

CoreLine Trunking Gen2

Full product name	LL200Z MB-SW 2xEP CU9 WH
EAN/UPC - Case	8719514108202

