Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or tr	ade mark:	PHILIPS
-----------------------	-----------	---------

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

Model identifier:	9290035541
-------------------	------------

Type of light source:	Type	of light	source:
-----------------------	------	----------	---------

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	G13 ROT		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with spe- cific dimmers

Product parameters

Product parameters				
Parameter		Value	Parameter	Value
		General product p	arameters:	
	nption in on- 00 h), rounded st integer	16	Energy efficiency class	D
dicating if it refe a sphere (360º)	s flux (φuse), in- ers to the flux in , in a wide cone rrow cone (90º)	2 500 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode pow pressed in W	ver (P _{on}), ex-	16,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00
(P _{net}) for CLS, 6	candby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimen-	Height	1 212	Spectral power dis-	See image
sions without	Width	28	tribution in the	in last page
separate con- trol gear, light-	Depth	28	range 250 nm to 800 nm, at full-load	

ing control parts and non- lighting con- trol parts, if any (millime- tre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordi-	0,382
		nates (x and y)	0,380
Parameters for LED and OLED light sources:			
R9 colour rendering index value	R9 colour rendering index value 0 Survival factor 0,90		0,90
the lumen maintenance factor	0,96		

(a)'-': not applicable; (b)'-': not applicable;

