## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| Supplier's name or | r trade mark: | PHILIPS |
|--------------------|---------------|---------|
|--------------------|---------------|---------|

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

| Model identifier: 92 | 290036076 |
|----------------------|-----------|
|----------------------|-----------|

| Type | of I         | ight  | sour | ce: |
|------|--------------|-------|------|-----|
| IVDC | <b>U</b> I I | ISIIL | JUUI | ··· |

| LED | Non-directional or directional: | NDLS  |
|-----|---------------------------------|---|
| E27 |                                 |   |
|     |                                 |   |
| MLS | Connected light source (CLS):   | No  |
| No  | Envelope:                       | -   |
| No  |                                 |   |
| No  | Dimmable:                       | No  |
|     | E27 MLS No No                   | MLS Connected light source (CLS):  No Envelope:  No |

## **Product parameters**

| Parameter   |  | Value                     | Parameter  | Value        |
|---|--|---------------------------|--|--------------|
|   |  | General product p         | arameters:   |              |
| ٠,  | nption in on-<br>00 h), rounded<br>st integer                                    | 13                        | Energy efficiency class  | Е            |
| dicating if it refe<br>a sphere (360º)            | s flux (фuse), in-<br>ers to the flux in<br>, in a wide cone<br>arrow cone (90º) | 1 521 in<br>Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 3 000        |
| On-mode pow<br>pressed in W                       | ver (P <sub>on</sub> ), ex-  | 13,0                      | Standby power (P <sub>sb</sub> ),<br>expressed in W and<br>rounded to the sec-<br>ond decimal  | 0,00         |
| (P <sub>net</sub> ) for CLS, 6                    | candby power expressed in W the second dec-                                      | -                         | Colour rendering in-<br>dex, rounded to the<br>nearest integer, or<br>the range of CRI-val-<br>ues that can be set   | 80           |
| Outer dimen-                                      | Height   | 120                       | Spectral power dis-  | See image    |
| sions without                                     | Width  | 60                        | tribution in the   | in last page |
| separate con-<br>trol gear, light-<br>ing control | Depth  | 60                        | range 250 nm to 800<br>nm, at full-load  |              |

| parts and non-<br>lighting con-<br>trol parts, if<br>any (millime-<br>tre)  |               |  |                |  |
|---|---------------|--|----------------|--|
| Claim of equivalent power <sup>(a)</sup>  | Yes           | If yes, equivalent power (W)           | 100            |  |
|   |               | Chromaticity coordinates (x and y)     | 0,434<br>0,403 |  |
| Parameters for LED and OLED li  | ight sources: | ,                                      |                |  |
| R9 colour rendering index value   | 0             | Survival factor                        | 0,90           |  |
| the lumen maintenance factor  | 0,93          |  |                |  |
| Parameters for LED and OLED mains light sources:  |               |  |                |  |
| displacement factor (cos φ1)  | 0,70          | Colour consistency in McAdam ellipses  | 6              |  |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. |               | If yes then replace-<br>ment claim (W) | -              |  |
| Flicker metric (Pst LM)   | 1,0           | Stroboscopic effect metric (SVM)       | 0,4            |  |

(a)'-': not applicable; (b)'-': not applicable;

