

# LIMEA CONNECT

SLI028111CW\_PW

Hermetic luminaire LIMEA CONNECT, with a power of 36 W, high light efficacy 147 lm/W. It has a very high degree of protection IP65, providing protection against the ingress of dust and water jets. IK08 class provides impact resistance. It shines with a cold light (6000K). Suitable for both surface and suspended mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.



Power	<b>36 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>5300 lm (360°)</b>	Colour temperature	<b>6000 K</b>
Colour of light	<b>CW</b>	Beam angle	<b>120 °</b>
IK	<b>08</b>	Degree of protection (IP)	<b>IP65</b>

## Technical data

---

Code	SLI028111CW_PW
Power	36 W
Nominal current	160 mA
Voltage	230 V
Energy consumption	36 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.98
Useful luminous flux*	5300 lm (360°)
Luminous flux**	4300 lm (360°)
Lamp efficacy	147 lm/W
Colour temperature	6000 K
Colour of light	CW
Beam angle	120 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	26000 h
Housing material	PC/PC
IK	08
Degree of protection (IP)	IP65
Colour	Gray
Dimension (AxBxC)	1200x64x60 mm
For use	Inside/Outside
Assembly method	On the ceiling, Suspended
Application	INT/EXT
Made in	PRC
Other	MAX 22 pcs per line ,


## Related documents

---



 User manual



 Declaration of Conformity



 Photometric file

