Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark:	PHILIPS
--------------------------------	---------

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

Model identifier:	9290023070
-------------------	------------

_	•			
Ivpe	ot	light	source	

LED	Non-directional or directional:	NDLS
E27		
MLS	Connected light source (CLS):	No
No	Envelope:	-
No		
No	Dimmable:	No
	E27 MLS No No	MLS Connected light source (CLS): No Envelope: No

Product parameters

Parameter		Value	Parameter	Value
		General product p	arameters:	I
	nption in on- 00 h), rounded st integer	13	Energy efficiency class	E
dicating if it refe a sphere (360º)	s flux (фuse), in- ers to the flux in , in a wide cone arrow cone (90º)	1 521 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 500
On-mode pow pressed in W	ver (P _{on}), ex-	13,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00
(P _{net}) for CLS, 6	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimen-	Height	120	Spectral power dis-	See image
sions without	Width	60	tribution in the	in last page
separate con- trol gear, light- ing control	Depth	60	range 250 nm to 800 nm, at full-load	

parts and non- lighting con- trol parts, if any (millime- tre)				
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	100	
		Chromaticity coordinates (x and y)	0,312 0,328	
Parameters for LED and OLED li	ght sources:			
R9 colour rendering index value	0	Survival factor	0,90	
the lumen maintenance factor	0,93			
Parameters for LED and OLED mains light sources:				
displacement factor (cos φ1)	0,71	Colour consistency in McAdam ellipses	6	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		If yes then replace- ment claim (W)	-	
Flicker metric (Pst LM)	0,5	Stroboscopic effect metric (SVM)	0,1	

(a)'-': not applicable; (b)'-': not applicable;

