Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: PHILIPS

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

Model identifier: 8711500632197

Type of light source:

Lighting technology used:	other FL	Non-directional or directional:	NDLS		
Light source cap-type	G13				
(or other electric interface)					
Mains or non-mains:	NMLS	Connected light source (CLS):	No		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	Yes		
Product parameters					

expressed in W expressed in W and rounded to the second decimal Networked standby power (P _{net}) - Colour rendering 80 index, rounded to the second decimal rounded to the second decimal or the nearest integer, or the range of CRI-values that can be set Outer Height 1514 Spectral power See image distribution in the in last page			i ioduct para	ineters	T		
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer60Energy efficiency classGUseful luminous flux (\$\$\phiuse\$), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone 	Parameter		Value	Parameter	Value		
mode (kWh/1000 h), rounded up to the nearest integerclassUseful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone5 240 in Sphere (360°)Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set4 000On-mode expressed in W59,4Standby power (Psb), expressed in W and rounded to the second decimal0,00Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal-Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set80Outer dimensions withoutHeight1514 28Spectral power distribution in theSee image in last page	General product parameters:						
indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)Sphere (360°)temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be setOn-mode power expressed in Wpower (Pon), expressed in W59,4Standby power (Psb), expressed in W and rounded to the second decimal0,00Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal-Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set80Outer dimensions withoutHeight1514 28Spectral power distribution in theSee image in last page	mode (kWh/10	00 h), rounded	60		G		
expressed in W expressed in W and rounded to the second decimal Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal Outer dimensions without Height 1514 Depth 28	indicating if it r in a sphere (3 cone (120 ^o) or i	efers to the flux 60°), in a wide		temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that	4 000		
for CLS, expressed in W and rounded to the second decimalindex, rounded to the nearest integer, or the range of CRI- values that can be setOuter dimensions withoutHeight1514Spectral distribution in theSee image in last page	On-mode p expressed in W	oower (P _{on}),	59,4	expressed in W and rounded to the	0,00		
dimensions withoutWidth28distribution in thein last pageDepth28	for CLS, expre	ssed in W and	-	index, rounded to the nearest integer, or the range of CRI- values that can be	80		
without Depth 28	Outer dimensions without	Height	1 514	Spectral power	See image		
Deptin 28		Width	28	distribution in the	in last page		
		Depth	28	1			

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load	
Claim of equivalent power ^(a)	-	lf yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,380 0,380

(a)_{'-'} : not applicable;

(b)'-' : not applicable;

