Product Data Sheet

GWA1201


Connected SMART HOME




Wireless connected device with Zigbee protocol from the ChoruSmart system that can be with Home Gateway for "CONNECTED SMART HOME" solutions, for residential and small offices, both for new builds and renovations. Zigbee technology is a secure and reliable technology in which data is encrypted and every node in the network ensures reachability across all devices (mesh network).

Output contacts	1 NA / NC 2 A (AC1) 240 V ac	Power supply	100 ÷ 240 V ac - 50/60 Hz
No. modules	1	No. output channels	1
Radio connections	Zigbee (IEEE 802.15.4)	Standard 201	4/53/EU, 2011/65/EU + 2015/863, EN 60669-2-1, EN
		60669-1	, EN 301 489-1, EN 301 489-17, EN 300 328, EN IEC
			63000
Working temperature	-5 ÷ +45 °C	Relative humidity (non-condensati	ve) Max 93%
Power output Zigbee	10 dBm	Dispersible max power (W)	2,6
Wiring terminals With scre		Terminal tightening capacity	Max. 1,5
		stranded cables (mm²)	
Terminal tightening ca	pacity Max. 1,5	Category	Axial 2-way switch connected
solid cables (mm²)			
No. input channels	2 (for local command replication or sending additional Zigbee	Input voltage	Mains supply voltage
	commands)		
IP degree	IP20 (with button key)	240 V ac Incandescent-halogen lamps 4-500 W	
240 V ac LED lamps	4-100 W	Loads piloted from electronic trans	formers 240 V ac 4-250 VA
LED colour	Blue	Local control	Via front push button (to complete with button key)
Power supply of EGO SMART plate Yes		Zigbee control extension if installed in an EGO SMART plate (Sfelf-(1)fizingthiem)command)	
Functions	Timed load control, indicative measurement of active power		
	and consumed energy		

DIMENSIONAL





TECHNICAL SYMBOLOGY



IP20 (with button key)

STANDARDS/APPROVALS

