Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources						
Supplier's name	e or trade mark:	PHILIPS				
Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL						
Model identifier: 8718291651697						
Type of light so	urce:					
Lighting techno	logy used:	МН	Non-directional or directional:	DLS		
Light source cap-type		E27				
(or other electric interface)						
Mains or non-m	nains:	NMLS	Connected light source (CLS):	No		
Colour-tuneable	e light source:	No	Envelope:	No		
High luminance light source:		No				
Anti-glare shield:		No	Dimmable:	No		
Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		74	Energy efficiency class	G		
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		4 500 in Narrow cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 200		
On-mode power (P _{on}), expressed in W		73,2	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	92		
Outer	Height	123	Spectral power	See image		
dimensions without	Width	97	distribution in the	in last page		
without	Depth	97		 		

separate control gear, lighting control parts and non- lighting control parts, if any		range 250 nm to 800 nm, at full-load				
(millimetre)						
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity	0,371			
		coordinates (x and y)	0,366			
Parameters for directional light sources:						
Peak luminous intensity (cd)	9 800	Beam angle in degrees, or the range of beam angles that can be set	40			

(a)'-': not applicable; (b)'-': not applicable;

