

# PRODUCT DATASHEET TruSys<sup>®</sup> PFM ENERGY RAIL 5P 3000

# TruSys® PERFORMANCE ENERGY RAIL 5 POLE | 5-pole mounting rail

A State of the sta

#### Areas of application

- Industry halls, high rack warehouse, garages, hardware stores

#### Product benefits

- Simple installation
- High flexibility thanks to two available lengths (1500 mm, 3000 mm and 1500 mm end rail)

#### **Product features**


- Through wired with 5 core cable
- Different lenghts available
- Electrical connection internal at the first luminaire, no external connection unit required
- Steel-sheet housing
- End-Rail without electrical and mechanical connectors



## **TECHNICAL DATA**

# **Dimensions & Weight**

Length	3150 mm
Width	70.2 mm
Height	38.8 mm
Product weight	3260.00 g



## Materials & Colors

Product color	White

# Application & Mounting

Ambient temperature range	-25+60 °C
Type of protection	IP20
Mounting type	Surface
Mounting location	Ceiling
With light source	No

## **Certificates & Standards**

Standards CE
--------------

## **EQUIPMENT / ACCESSORIES**

- Various accessories available

#### **DOWNLOAD DATA**

	Documents and certificates
PDF	User instruction

CAD/BIM files
 CAD_STEP_3D
Tender texts

# LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075354777	Shipping box 1	3,170 mm x 88 mm x 56 mm	3797.00 g	15.62 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.